

22/2 RISER RATED, UNSHIELDED SECURITY & CONTROL CABLE




22 AWG 2 Stranded Conductors, Unshielded

Ratings CMR, CL3R, FT4
Approvals ETL Listed

Construction

Conductor 22 AWG 7 Strand Bare Copper
Conductor Count 2
Insulation PVC (0.011" nom.)
Insulation Colors Black, Red
Lay Length Straight
Shielding N/A
Rip Cord Yes
Jacket PVC (0.017" nom.)
Overall Diameter 0.135" nom.
Print Legend ADI PRO P/N: RN-xxxxOXYGEN FREE
2C22 3180662 C(ETL)US CL3R 75C,
CMR FT4 ROHS LOT#xxxxxxxxFT



Properties

Operating Voltage 300 Volts max.
DC Resistance 16.9 Ohms/1000' at 20°C
Capacitance 18.5pF/ft. nom.
Temperature -20°C to 75°C
Flame Rating UL 1666 (Riser);
CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes
Country of Origin CHINA

PART#	COLOR	LENGTH	BOX
RN-85SR501	WHITE	500FT	SPEED COIL
RN-85SR505	ORANGE	500FT	SPEED COIL
RN-85SR502	BLUE	500FT	SPEED COIL
RN-85SR101	WHITE	1000FT	EXPRESS BOX



For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands