CA2200A

2/4/8/16-BUTTON CIAO MODULE. SIMPLEBUS 2

Ciao series button module for Simplebus 2 system. Front panel in technopolymer, resistant to atmospheric agents (IP54 protection rating and paint with anti-UV treatment) and acts of vandalism (IK08 protection rating). To be finished with 2/4/8/16 call buttons (art. CA9210, CA9211, CA9212 and 2 x CA9212 respectively), available to purchase separately. Supplied with a surface mounting bracket. Can be installed alongside (horizontally or vertically) up to 4 button modules. For use in conjunction with art. CA2100A.

CA2200A

2/4/8/16-BUTTON CIAO MODULE. SIMPLEBUS 2

COMPATIBLE SYSTEMS	
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Maximum absorption (W)	0.62

HARDWARE FEATURES	
Number of push-buttons (n°)	16

SETTINGS	
Backlight brightness	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV

GENERAL FEATURES	
Backlight colour	White
Call type	Push-buttons
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
IP protection rating	IP54
Type of buttons	Mechanical

MAIN FEATURES	
Vandal Resistant rating (IK code)	IK08
Height (mm)	172
Width (mm)	100
Depth (mm)	28
Product weight (g)	250

The technical specifications are subject to change without prior notice.

CA2200A

2/4/8/16-BUTTON CIAO MODULE. SIMPLEBUS 2

MAIN FEATURES	
Operating temperature (°C)	-25 ÷ 55
Supply voltage	33VDC

GENERAL DATA	
Type of finishing materials	Technopolymer
Product color	Grey RAL 9006

MOUNTING/INSTALLATION	
Wall-mounted	Yes

The technical specifications are subject to change without prior notice.