**UT9310M**

# MAGNETIC INDUCTION MODULE, ULTRA

Module with coil for hearing impaired users, for Ultra entrance panel, compatible with all systems. Allows hearing impaired users with hearing aids featuring the T function to hear the audio from the external unit. Anodised aluminium alloy front panel. Dimensions: 1 Ultra module. Dimensions: 100x90x35 mm

## AWARDS

DESIGN MILANO

**UT9310M**

# MAGNETIC INDUCTION MODULE, ULTRA

| GENERAL DATA | |
|---|---|
| Type | Modular |
| Height (mm) | 90 |
| Width (mm) | 100 |
| Depth (mm) | 35 |
| Product color | Aluminium |
| Flush-mounted | Yes, with a dedicated accessory |
| Wall-mounted | Yes, with a dedicated accessory |

| COMPATIBLE SYSTEMS | |
|---|---|
| Audio/video Simplebus 2 with power supply art. 4888C | Yes |
| Audio/video Simplebus 2 with power supply art. 1210/1210A | Yes |
| Audio Simplebus 2 with power supply art. 1210/1210A | Yes |
| Audio/video Simplebus 1 | Yes |
| Audio Simplebus 1 | Yes |
| ViP | Yes |

| ELECTRICAL CHARACTERISTICS | |
|---|---|
| Type of power supply | Power supply from video door entry bus |
| Supply voltage | 33VDC |
| Absorption in stand-by (W) | 0.73 |
| Maximum absorption (W) | 8 |

| ENVIRONMENTAL AND COMPLIANCE FEATURES | |
|---|---|
| Operating temperature (°C) | -25 ÷ 55 |
| Operating humidity (RH max) (%) | 25 ÷ 95 |
| Environmental class | III |
| Certifications | RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |

The technical specifications are subject to change without prior notice.