SSF™ Fiber Optic Feed-thru Adapters provide easy cable connections. Available in simplex and duplex SC/SC and LC/LC configurations for single-mode (OS2 or 9/125 µm) and multimode fibers (OM2, OM3, OM4 or 50/125 µm).

SSF™ Hybrid Adapters are available in single-mode or multimode and SC to LC.

Feed-thru-style keystone inserts for standard wall plates are also available in LC and SC configurations.



FEATURES AND BENEFITS

- Meets TIA/EIA-568-B.3, TIA/EIA-604 FOCIS transmission standards
- Zirconia ceramic split sleeve
- Insertion loss: 0.1 dB average

PART NUMBER	STYLE	CONNECTOR	SLEEVE	MOUNT TYPE	FIBER TYPE
FEED-THRU ADAPTERS					
SSF-DLCLC-MMADP	Duplex	LC to LC	Ceramic	Flange	OM2/OM3/OM4
SSF-DLCLC-SMADP	Duplex	LC to LC	Ceramic	Flange	OS2
SSF-DLCLC-SMAPCADP	Duplex	LC APC to LC APC	Ceramic	Flange	OS2
SSF-DSCSC-MMADP	Duplex	SC to SC	Ceramic	Flange	OM2/OM3/OM4
SSF-DSCSC-SMADP	Duplex	SC to SC	Ceramic	Flange	OS2
SSF-DSCSC-SMAPCADP	Duplex	SC APC to SC APC	Ceramic	Flange	OS2
SSF-SLCLC-MMADP	Simplex	LC to LC	Ceramic	No flange	OM2/OM3/OM4
SSF-SLCLC-SMADP	Simplex	LC to LC	Ceramic	No flange	OS2
SSF-SSCSC-MMADP	Simplex	SC to SC	Ceramic	Flange	OM2/OM3/OM4
SSF-SSCSC-SMADP	Simplex	SC to SC	Ceramic	Flange	OS2
SSF-SLCLC-SMAPCADP	Simplex	LC/APC to LC/APC	Ceramic	No flange	OS2
SSF-SSCSC-SMAPCADP	Simplex	SC/APC to SC/APC	Ceramic	Flange	OS2
HYBRID ADAPTERS					
SSF-SCLC-MMADP	Simplex	Male SC to Female LC	Ceramic		OM2/OM3/OM4
SSF-SCLC-SMADP	Simplex	Male SC to Female LC	Ceramic		OS2
SSF-LCSC-MMADP	Simplex	Male LC to Female SC	Ceramic		OM2/OM3/OM4
SSF-LCSC-SMADP	Simplex	Male LC to Female SC	Ceramic		OS2

All right reserved. Subject to change without notice
Copyright 2012 Cleerline Technology Group, LLC