Product: **810**
RG213/U Type 52 Ω Non-Plenum
RF 50 Ω Video, Wireless Mic Distribution

CONDUCTOR PARAMETERS	
Number of Conductors	1
AWG Size	12
Conductor Stranding	7 x 20
Conductor Type	Bare Copper
Nom. DCR	1.9 Ω/1000 ft
INSULATION PARAMETERS	
Insulation Type	Foam FEP
Insulation Thickness	.280 in
Insulation Color Code	White Dielectric
SHIELDING PARAMETERS	
Shield Type	100% Aluminium Foil
Shield Type 2	95% Tinned Copper
ELECTRICAL CHARACTERISTICS	
Nom. Cap. Between Conductors	16.5 pf/ft
Nom. Impedance	52 Ω +/-3 Ω
Nom. Velocity of Propogation	80%

OVERALL CONSTRUCTION PARAMETERS	
Number of Conductors	1
Jacket Type	PVC Flex
Nom. Cable O.D.	.405 in
Plenum	No
NEC UL Rating	CM
RG Size	RG-213 Type
RoHS Compliant	Yes
Bend Radius	4.0 in
Pull Tension	187 lbs
Cable Weight	105 lbs

OVERALL ELECTRICAL CHARACTERISTICS	
UL Flammability	UL 1685
Operating Range	40 to 75°C
UL Voltage Rating	300