HUBBELL
Premise Wiring

HFCB14 Series Indoor/Outdoor Tight Buffer, 24 strand, Plenum, OS2, SM, Yellow Jacket

By Hubbell Premise Wiring
Catalog # HFCB14024PS

HFCB14 Series Indoor/Outdoor Tight Buffer, 24 strand, Plenum, OS2, SM, Yellow Jacket

Features

- Multi-purpose outdoor to building riser or horizontal infrastructure all with a single cable design
- Flexible cost-saving design for simple installation and termination
- Eliminates the need for transition points with plenum rated jacket
- Enhanced water blocking system inside the core cable with fungus and sunlight resistant jacket
- Made in USA with Bend Insensitive Corning glass

Application

Data Tranmission

General

Attenuation	0.5/0.5 Db per Kilometer
Cable Rating	Plenum
Catalog Number	HFCB14024PS
Color	Yellow
Material - Jacket	PVC
Series	Fiber
Specifications	• Non-Armored • Cable Diameter in (mm) - 0.29 (7.3) • Cable Weight (lb/kft) - 34 • Construction - Single Unit, DryGel Water Blocking • Fiber Coating - 900 Micron PVC Tight Buffer
Style	Tight Buffer
Sub Brand	FiberHubb
Temperature Rating	0 Degrees C to 70 Degrees C
Type	Cable
UPC	662620373805

Electrical Ratings

Wavelength	1310/1550 Nanometers

Conductor Related

Fiber Size	OS2
Fiber Type	OS2, SM
Number of Fibers	24
Strands	24

Certifications And Compliance

Industry Standard(s)	• ANSI/ICEA S-83-596 • NFPA-262/UL910/CSA FT-6 • Telcordia GR-409 • TIA-568.3-D

Product Assets

Literature - FiberHUBB Universal Cable Specifications - HFCB14024PS

©2025 Hubbell Incorporated. All rights reserved