1682

IKALL VIP AUDIO ONLY SPEAKER

Audio unit for ViP system. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. For fitting in modules: part. 33400, 33401, 33402. Dimensions: 102x55x38 mm.

1682

IKALL VIP AUDIO ONLY SPEAKER

GENERAL DATA	
Type	Audio and video unit
Height (inch) (in)	4.02
Width (inch) (in)	2.17
Depth (inch) (in)	1.69
Product weight (oz) (oz)	7.05
Product color	White
Type of finishing materials	ABS

COMPATIBLE SYSTEMS	
Vip system	Yes

AUDIO FEATURES	
Microphone	9.7 (ø), omnidirectional
Loudspeaker	50mm (Ø), 8 Ohm, 0.2W

ELECTRICAL CHARACTERISTICS	
Supply voltage	33VDC

HARDWARE FEATURES	
Clamps	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Removable terminals	Yes
Number of inputs (n°)	1
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)
Communication ports	Ethernet

SETTINGS	
Loudspeaker volume	Yes

The technical specifications are subject to change without prior notice.

1682

IKALL VIP AUDIO ONLY SPEAKER

NETWORK AND COMMUNICATION PROTOCOLS	
Type of LAN network	Ethernet 10 Mbit/s

PROGRAMMING MODE	
ViP Manager software	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011), RED 2014/53/UE (EN 62311:2008, EN 62368-1:2014, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS	
Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes

The technical specifications are subject to change without prior notice.