High-Flex Audio

14/2C STR (41/30) OFC HI-FLEX

CL3/FPL

1U1402H2B1

1.0 SCOPE:

1.1 This cable consists of 2 conductors 14 AWG stranded bare copper; color-coded PVC insulation; overall white sunlight resistant PVC Jacket.

Type CL3/FPL
UL Standard 13
NEC Article 725
UL 1581

2.0 CONSTRUCTION:

2.1 CONDUCTOR:

2.1.1 Material: Bare Copper
2.1.2 Size: 14 AWG
2.1.3 Construction: 41/30
2.1.4 OD: .106" nom.
2.4.5 Lay Length: 3.2"

2.2 INSULATION:

2.2.1 Material: PVC
2.2.2 Wall Thickness: .014" nom.
2.2.3 Color code: 1-Black, 2-Red

2.3 JACKET:

2.3.1 Material: PVC
2.3.2 Wall Thickness: .018" nom.
2.3.3 OD: .264" nom.
2.3.4 Color: White
2.3.5 Ripcord under jacket
2.3.6 Markings: PAIGE 1U1402H2B5
14/2C STR CL3/FPL SUN RES (****)
75° C XXXX (***) ROHS COMPLIANT
(**) (*)

2.4 ELECTRICAL PROPERTIES

2.4.1 Temperature: -20°C to 60°C
2.4.2 Voltage: 300 Volt
2.4.3 Capacitance: 30 pF/ft nom @ 1 MHz
2.4.4 DC Resistance: 2.52 Ohms/M' @ 20°C

2.5 PUT-UPS:

2.5.1 1,000' Box
2.5.2 Weight 42 lbs / 1000'

(*) Ascending / Descending Footage to Repeat Every 2 Feet.
(**) Manufacturer's lot number (for traceability)
(***) Cable Mill Factory Identification
(****) UL or ETL Listed & CSA Certified or C(UL)US Listed Acceptable

The information and specifications described herein are subject to error or omission and to change without notice.

Paige provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Paige be liable for any damages (including consequential, indirect, incidental, special, punitive or exemplary damages) whatsoever, even if Paige has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

We want to hear from you!
200 Sheffield St, Suite 302
Mountainside, NJ 07092

Tel: 888.423.8947 info@paigeelectric.com www.paigedatacom.com