Downloaded: January 22, 2026

USB-C® 11-in-1 Hybrid DisplayLink and DP Alt Mode Triple 4K Docking Station with HDMI®, DisplayPort™, Ethernet, USB, 3.5mm Audio and Power Delivery up to 100W **SKU: C2G54538**

The USB-C® Hybrid Triple 4K Display Docking Station with DisplayLink and DP Alt Mode transforms USB-C enabled laptops into total desktop solutions through a single USB-C connection – allowing them to have more video outputs, more connected peripherals, and quick data transfers, all while keeping the laptop charged and ready to go.

This docking station supports crisp, high definition images and video when connecting one, two, or three 4K displays. When connecting to the HDMI port labeled "DP Alt Mode", be sure that the connected laptop supports DP alt mode.

The front USB-A and USB-C 3.2 Gen 2 ports support BC 1.2 for quick mobile device charging and data transferring up to 10Gbps, while the two USB-A Gen 1 ports on the rear support 5Gbps data transfers. The Ethernet port allows for reliable internet connectivity with file transfer speeds up to 1000Mbps.

The included 130W power supply keeps the connected laptop charged and ready to go with 100W power delivery while supporting connected devices, such as keyboards, mice, portable hard drives, and other peripherals. The maximum power capacity depends on how much power the connected adapter can supply. The right amount of power is necessary to keep the laptop battery charged, for all connected devices to function, and for the dock to provide that connectivity. Laptops or tablets that require more than 100W may charge at lower speeds.

The USB-C Hybrid Triple 4K Display Docking Station maximizes desktop space while providing a single cable solution for Windows, Mac OS devices (including M1X), and Chrome OS. Download and install the latest DisplayLink drivers at https://www.synaptics.com/products/displaylink-graphics/downloads.

Note: The latest DisplayLink drivers must be downloaded to support the first and second connected displays. To use the HDMI port labeled "DP Alt Mode", the connected laptop must support DP alt mode.

MAXIMUM SUPPORTED RESOLUTIONS

3 Displays: 4K (3840 × 2160) at 30Hz
2 Displays: 4K (3840 × 2160) at 60Hz
1 Display: 4K (3840 × 2160) at 60Hz (DP Alt Mode HDMI port supports 4K 30Hz)
Note: HDMI output labeled "DP Alt Mode" to be used with DP alt mode laptops
Single Screen Support on M1 Macbooks

PORTS

2x HDMI (DisplayLink) Ports: Connect to HDMI port 1 or port 2 for a single 4K display or dual 4K displays, supporting audio and video.
2x DisplayPort (DisplayLink) Ports: Connect to DisplayPort port 1 or port 2 for a single 4K display or dual 4K displays, supporting audio and video.
1x HDMI (DP Alt Mode) Port: Connect to the HDMI port labeled "DP Alt Mode" when using a triple display setup with a connected laptop that supports DP alt mode.
3x USB-C: The left side USB-C port delivers up to 100W of power to the connected laptop, the front battery labeled USB-C Gen 2 port supports 10Gbps and BC 1.2 for quick mobile device charging, and the front USB-C Gen 1 port supports data transferring up to 5Gbps.
3x USB-A: Connect storage devices and transfer data up to 5Gbps through the two rear USB-A Gen 1 ports, with the front USB-A Gen 2 port supporting 10Gbps and BC 1.2 for quick mobile device charging.
Gigabit Ethernet: Connect to a local network for network and internet access.
Audio Combo Jack: Connect a headset microphone or speakers for audio output.

Note: Only a single video output is supported with the original M1 MacBook. Newer Apple devices (M1 Max and M1 Pro, etc.) are not impacted and support dual monitors.

ADDITIONAL TECHNICAL SPECS

Electrical Specifications

- Power Adapter: Electrical: Input AC: 100-240V; Input Dock: 24V, 4A
- Power Consumption: 130W
- USB-C Power Delivery: 100W

Physical Specifications

- Operating Temperature: 0°C to +70°C
- Storage Temperature: -10°C to +55°C; 0 to 85% RH (Non-Condensing)

Physical Characteristics

- Cables: Color: Black
- Docking Station: Dimensions: 7.52in (191mm) x 1.25in (31.8mm) x 3.35in (85mm) LxHxD
- Material: Housing: Plastic (ABS+PC), black, covered by soft silicone sheet
- Product Certifications: RoHS, REACH, Prop65, CE, FCC

Package Contents

1 x USB-C Hybrid Triple Display Docking Station
1 x 1.5ft (0.5m) Male USB-C to Male USB-C Cable
1 x 1.5ft (0.5m) Male USB-C to Male USB-A Cable
1 x 130W Power Supply with US, EU, & UK Plugs
1 x Manual

Specifications

Dimensions & Measurements

Power Delivery	100 W
Shipping Weight	2.23 lbs (1 kg)
Storage Humidity Max	85% RH (Non-Condensing)
Storage Humidity Min	85% RH (Non-Condensing)

Characteristics & Features

Application	• Commercial • Residential
Color	Black
Connector 1	(1) USB-C Male
Connector 2	• (1) 3.5mm Female • (1) RJ-45 Female • (2) DisplayPort Female • (3) HDMI Female • (3) USB-A Female • (3) USB-C Female
Product Type	Docking Station
TAA Compliant	No
UPC	757120545385
Video Input Support	• DisplayPort • HDMI
Video Output Support	USB-C
Video Resolution	• 4K • 4K @ 30Hz • 4K @ 60Hz

Certifications & Warranties

Certifications	• CE • NDAA 889 • Prop 65 • REACH • RoHS • TSCA
Data Transfer Rate	10 GBPS
Warranty	5 years

Source: https://www.legrandav.com/products/cables_and_connectivity/docks_and_usb_hubs/usb-c-hybrid-dual-display-dock/c2g54538