Capture powered by Eagle Eye Networks

Capture Cloud VMS

WHAT IS THE CAPTURE CLOUD VMS?

The Capture Cloud VMS is a fully managed cloud video surveillance solution, delivering an end-to-end video management system that's simple to deploy and easy to use. It supports all modern browsers and works on Windows, Mac, even Linux with no plugins to install.

FULLY MOBILE

View video anytime, anywhere. The fully functional iOS and Android applications provide complete access to live and recorded video and can also be used to install, configure and manage the system.



GOT CLOUD?

Capture Cloud provides a cloud based, video management system. The Bridge is installed onsite, connects to your cameras, records video locally, and then securely synchronizes both video and meta data to the Capture Cloud Data center. It's a robust, secure appliance specifically designed to overcome the demands of transmitting high-resolution video through the Internet.

COMPREHENSIVE CAMERA SUPPORT

We believe camera compatibility is important. There's no need to be locked into a single camera vendor. Businesses need the flexibility to work with the cameras that they choose. Bridges and CMVRs support ONVIF Profile S IP cameras. Combo Bridges and CMVRs support IP as well as NTSC and PAL analog cameras. For an up to date list of all compatible cameras visit www.een.com/cameras.

WORRY FREE MANAGEMENT

All of the software in the Capture Cloud and firmware on the Bridge is managed and updated by Eagle Eye Networks.

SECURITY SIMPLIFIED

With Eagle Eye Complete Privacy Encryption™, video is fully encrypted during transmission and at rest. The Bridge has no open ports to the Internet, eliminating security vulnerabilities commonly found in other systems and requiring no router or firewall adjustments.

Rack Bridge

301 / 303 / 303G / 401 / 401ai /403G / 501 / 701 /901

The Bridge acts as a gateway from your premises to the Cloud Data Center where your video is stored and managed by the Cloud Cloud VMS. It provides video buffering, a secure connection, bandwidth management, and monitoring of cameras.

These 1U rack-based bridges are designed to fit in standard equipment rack. The rack mount bridges are offered in a range of sizes to support larger number of cameras. Versions are available with analog camera interfaces to allow direct connection of existing NTSC and PAL cameras. Versions are also available with integrated PoE ports for direct connection of IP cameras.

RECORDING FEATURES

- Video encrypted in transit and at rest
- Fully cloud managed
- Intelligent Bandwidth Management with local buffering
- Motion or continuous recording
- Optional audio recording

WEB INTERFACE & MOBILE FEATURES

- Native iOS and Android apps
- View live and recorded video
- Compatible with all modern browsers
- Motion detection with alerts
- Map and floorplan display

SYSTEM ADMINISTRATION

- 100% browser-based; no software
- Granular user permissions
- Multi-site support
- Point and click video sharing
- Centralized management

Rack Bridge 301 / 303 / 303G / 401 / 401ai / 403G / 501 / 701 / 901

02.2026



NETWORK FEATURES

- Automatic network configuration
- Secure camera network (dual network ports)
- No inbound connections needed
- Packet loss detection/reporting
- Network disconnected alerts

MANAGEMENT FEATURES

- Remote management
- Automatic camera discovery
- Automatic camera configuration
- Advanced motion detection
- Local video buffering
- Configuration synced to Cloud
- Camera trouble alerts
- Internet outage alerts
- Fully cloud managed

STANDARD SUPPORT

- Free of charge with an active subscription
- Warranty – 2 years
- 24/7 email and web support
- 8 a.m. to 6 p.m. phone support

MODEL	BRIDGE 301	BRIDGE 303G	BRIDGE 401	BRIDGE 401ai	BRIDGE 403G	BRIDGE 501	BRIDGE 701	BRIDGE 901
Max Cameras*	Up to 20 IP Cameras @4MP	Up to 20 IP Cameras @4MP	Up to 35 IP Cameras @4MP	Up to 35 IP Cameras @4MP	Up to 35 IP Cameras @4MP	Up to 50 IP Cameras @4MP	Up to 150 IP Cameras @4MP	Up to 300 IP Cameras @4MP
Max Analytic Count*	5	5	10	30	10	10	20	30
LPR Support*	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Video Buffer	2 days on premises	2 days on premises	2 days on premises	2 days on premises	2 days on premises	2 days on premises	2 days on premises	2 days on premises
POE Camera Ports	None	8 port, Class 3	None	None	8 port, Class 3	None	None	None
Network Ports	Dual Gigabit	Dual Gigabit	Dual Gigabit	Dual Gigabit	Dual Gigabit, 16×1G ports	Dual Gigabit	Dual 10Gbps	Dual 10Gbps
Video Output**	VGA (1), DVI (1)	HDMI (1), VGA (1)	VGA (1), HDMI (1), DP (1)	HDMI (4)	VGA (1), HDMI (1)	VGA (1), HDMI (1), DP (1)	VGA (1), HDMI (1), DP (1)	VGA (1), HDMI (1), DP (1)
Dimension	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U	427 x 251 x 45 mm 16.81 x 9.88 × 1.75 in 1U	427 × 251 × 45 mm 16.81 × 9.88 × 1.75 in 1U
Weight	3.29 kg 7.25 lbs	3.76 kg 8.28 lbs	4.14 kg 9.13 lbs	3.97 kg 8.75 lbs	3.89 kg 8.58 lbs	4.31 kg 9.50 lbs	4.31 kg 9.50 lbs	4.31 kg 9.50 lbs
Maximum Power Consumption	Internal 100-240 VAC, 65 W	Internal 100-240 VAC, 42 W	Internal 100–240 VAC, 50 W	Internal 100–240 VAC, 130 W	Internal 100–240 VAC, 60 W	Internal 100–240 VAC 120 W	Internal 100–240 VAC 300 W	Internal 100–240 VAC 120 W
Operating Temperature Range	0–35 °C 32–95 °F	0–35 °C 32–95 °F	0–35 °C 32–95 °F	0–35 °C 32–95 °F	0–35 °C 32–95 °F	0-35° C 32-95° F	0–35 °C 32–95 °F	0–35 °C 32–95 °F
Operating Humidity Range	0–70%	0–70%	0–70%	0–70%	0–70%	0–70%	0–70%	0–70%
Certifications	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, BIS, RCM, RoHS, WEEE	FCC, UL, PSE, CE, (S&E)	FCC, UL, PSE, CE, (S&E)
Eagle Eye Rapid Replacement Part Numbers	EN-RR301-1 (Monthly) EN-RR301-12 (Yearly)	EN-RR303g-1 (Monthly) EN-RR303g-12 (Yearly)	EN-RR401-1 (Monthly) EN-RR401-12 (Yearly)	EN-RR401ai-1 (Monthly) EN-RR401ai-12 (Yearly)	EN-RR403g-1 (Monthly) EN-RR403g-12 (Yearly)	EN-RR501-1 (Monthly) EN-RR501-12 (Yearly)	EN-RR701-1 (Monthly) EN-RR701-12 (Yearly)	EN-RR901-1 (Monthly) EN-RR901-12 (Yearly)

*Typical - please utilize the Eagle Eye VMS Bridge Wizard for precise capacity