Powered Subwoofers

Protege FS12 12″ Floor Standing Sub

ITEM	U/M
FS12	Each

One dual-drive subwoofer with 12″ front-firing polypropylene-coated fiber composite woofer, 12″ down-firing passive radiator and Class D Amp with 300 watts RMS, 600 watts peak. Anti-clipping circuitry assures high output with low distortion. Black wood grain vinyl finish and dampened rubber feet.

- Amplifier Type: Class D Amp
- Power Rating Continuous: 300 Watts RMS
- Power Rating Peak: 600 Watts Peak
- Frequency Response: 28Hz - 150Hz
- Subwoofer Output: 106dB SPL
- Inputs: Left & Right Line Level, LFE
- Outputs: Line Level High-Pass
- Protection: Anti-Clipping Circuitry
- Power On/Off: Auto Sensing
- Phase Switch: 0 - 180˚
- Crossover: 50Hz - 150Hz; Bypass
- Finish: Black Wood Grain Vinyl
- Dampened Rubber Feet
- Dimensions (H x W x D): 16⅝″ x 14½″ x 15½″
- Weight: 35 lbs

Protege FS10 10″ Floor Standing Sub

ITEM	U/M
FS10	Each

One dual-drive subwoofer with 10″ front-firing polypropylene-coated fiber composite woofer, 10″ down-firing passive radiator and Class D Amp with 250 watts RMS, 500 watts peak. Anti-clipping circuitry assures high output with low distortion. Black wood grain vinyl finish and dampened rubber feet.

- Amplifier Type: Class D Amp
- Power Rating Continuous: 250 Watts RMS
- Power Rating Peak: 500 Watts Peak
- Frequency Response: 30Hz - 150Hz
- Subwoofer Output: 103dB SPL
- Inputs: Left & Right Line Level, LFE
- Outputs: Line Level High-Pass
- Protection: Anti-Clipping Circuitry
- Power On/Off: Auto Sensing
- Phase Switch: 0 - 180˚
- Crossover: 50Hz - 150Hz; Bypass
- Finish: Black Wood Grain Vinyl
- Dampened Rubber Feet
- Dimensions (H x W x D): 15⅛″ x 13¼″ x 14″
- Weight: 27 lbs

Protege FS8 8″ Floor Standing Sub

ITEM	U/M
FS8	Each

One dual-drive subwoofer with 8″ front-firing polypropylene-coated fiber composite woofer, 8″ down-firing passive radiator and Class D Amp with 200 watts RMS, 400 watts peak. Anti-clipping circuitry assures high output with low distortion. Black wood grain vinyl finish and dampened rubber feet.

- Amplifier Type: Class D Amp
- Power Rating Continuous: 200 Watts RMS
- Power Rating Peak: 400 Watts Peak
- Frequency Response: 32Hz - 150Hz
- Subwoofer Output: 100dB SPL
- Inputs: Left & Right Line Level, LFE
- Outputs: Line Level High-Pass
- Protection: Anti-Clipping Circuitry
- Power On/Off: Auto Sensing
- Phase Switch: 0 - 180˚
- Crossover: 50Hz - 150Hz; Bypass
- Finish: Black Wood Grain Vinyl
- Dampened Rubber Feet
- Dimensions (H x W x D): 13⅝″ x 11¾″ x 12½″
- Weight: 20 lbs

PAS-WIR-SUB-KIT Wireless Audio Subwoofer Kit

U/M
Kit

Consisting of one transmitter and one receiver the wireless audio receiver mounts to the back of the subwoofer. Expand your system with up to three additional receivers.

- Wireless connectivity range of 30 + feet
- Interference free - 5Ghs FHSS Technology
- Receiver mounts directly to the subwoofer
- Kit can expand up to four receivers
- All cables included

PAS-WIR-RX Wireless Audio Subwoofer Receiver

U/M
Each

Additional Receiver for Subwoofer Wireless Audio Kit. Each transmitter can accomodate up to four receivers.

- Wireless connectivity range of 30+ feet
- Interference free - 5Ghs FHSS Technology
- Receiver mounts directly to the subwoofer
- USB powered directly from Subwoofer USB port
- All cables included