IK04N1ZA

IP Vandal-Resistant Dome Camera 4MP 2.8–12mm

NEXT SERIE

Next series vandaldome IP camera with IK10 protection rating. Ideal for all installations in which the camera is in a position at risk of tampering or damage. 2.8?12 mm motorised lens with autofocus function, resolution 4MP@30 fps. IR LEDs with a range of 30 metres (SMART IR), ONVIF compatible (Profile G,M,S,T). Video analysis functions: Intrusion into an area (distinction between humans/vehicles), line crossing (distinction between humans/vehicles), object abandoned/removed function. WDR 120Db, compression H.265+/H.265/H.264+/H.264/MJPEG, SD slot (max. 256GB). Audio: 1 in, 1 out, built-in microphone. IP67 waterproof die-cast aluminium enclosure, power supply 12 VDC / PoE IEEE802.3af. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Compatible accessories: JBA-KA, CMA-KTBBA, WMA-KTBBA, PMA-A, AMA-A, CMA-KCAMA.

AWARDS

NDAA COMPLIANT

IK04N1ZA

IP Vandal-Resistant Dome Camera 4MP 2.8–12mm

MAIN FEATURES	
Camera sensor	1/3" CMOS Ultra Starlight
Lens type	Motorized
Lens optical varifocal dimensions (mm)	2.8 ÷ 12
Horizontal FoV (°)	92÷31
Vertical FoV (°)	48÷17
Diagonal FoV (°)	112÷35.6
Electronic shutter (s)	1/1÷1/100000
Sensitivity	0.004 (Colori), 0 (Bianco e nero led IR ON)
Signal/noise ratio (dB)	>50
Video trasmission	Triple streaming
Management software	Comelit CCTV Manager
Video resolution	4MP

DORI	
Detection (min - max) (m)	64 ÷ 189
Observation (min - max) (m)	26 ÷ 75
Recognition (min - max) (m)	13 ÷ 38
Identification (min - max) (m)	6 ÷ 19

SOFTWARE/FIRMWARE SPECIFICATIONS	
Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Audio compression	G711A/U
Frame rate	30fps
Bit rate range (Mbit/s)	0.06 ÷ 6
Protocols supported	DDNS, DHCP, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, QoS, RTCP, RTP, RTSP, SMTP, UDP, UPnP, P2P, ONVIF, SNMP, IEEE 802.1x, RTMP
Updating firmware using network	Yes
Users connected at the same time	6 (live)
Remote viewer from browser	Edge, Firefox, Chrome, Safari

The technical specifications are subject to change without prior notice.

IK04N1ZA

IP Vandal-Resistant Dome Camera 4MP 2.8–12mm

SOFTWARE/FIRMWARE SPECIFICATIONS	
Remote control by mobile	APP Comelit CCTV
Latest firmware version	5.2.3.3636B250704.ID13.U1(07F07)

FUNCTIONS	
Motion detection	Yes
Video analytics	Scene change detection, Video tampering detection, Line crossing detection (human / vehicle classification), Object abandoned / missing detection, Region intrusion detection (human / vehicle classification), Blurred image detection
Optimal people detection distance (m)	15
Optimal vehicle detection distance (m)	20
Back light compensation (BLC)	BLC
Digital effects	Mirror (Horizontal, Vertical, 180° rotation), ROI zones, Saturation, Brightness, Contrast, Sharpness, Image flip
Wide Dinamic Range (WDR)	WDR (120dB)
Enhanced DNR control	3D-DNR
White balance control	Automatic, Indoor, Manual, Outdoor
Display brightness control	Yes
Image flip	Yes
Automatic gain control (AGC)	Yes
Camera titling	Yes

HARDWARE SPECIFICATIONS	
IR LED lighting distance	30m
Vandal Resistant rating (IK code)	IK10
IP protection rating	IP67
Audio Inputs/Outputs	1 + Mic / 0
LAN output type	Ethernet 10/100 Mbit/s (RJ45)
Support SD card (card not included)	Micro-SD (256GB max)

GENERAL DATA

The technical specifications are subject to change without prior notice.

IK04N1ZA

IP Vandal-Resistant Dome Camera 4MP 2.8–12mm

Supply voltage	12VDC
Max absorption (W)	7.5
PoE power supply	Standard IEEE 802.3af
Type of power supply	PoE, External power supply
Diameter (mm)	141
Height (mm)	100
Product weight (g)	876
Type of finishing materials	Die-cast aluminum, High Impact Polycarbonate
Product color	White
Operating temperature (°C)	-30 ÷ 60
Operating humidity (RH max) (%)	25 ÷ 95

The technical specifications are subject to change without prior notice.

IK04N1ZA

IP Vandal-Resistant Dome Camera 4MP 2.8–12mm

ACCESSORIES

CMA-KCAMA

FLUSH-MOUNT CEILING BACKPLATE, ADVANCE VANDALDOME

This accessory is used for flush mounting Advance series vandaldome cameras, making them more discreet and less exposed to tampering attempts. For model compatibility please refer to the diagram in the download section.

WMA-KTBBA

ADVANCE NEXT WALL BACKPLATE

Wall-mounting bracket for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

CMA-KTBBA

ADVANCE NEXT CEILING BACKPLATE

Ceiling-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

PMA-A

ADVANCE ADVANCE NEXT BEUGEL OP PAAL POLE-MOUNTING BACKPLATE

Pole-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section. Pole diameter from 80 to 140 mm

JBA-KA

ADVANCE NEXT CONNECTION BOX IP66

Junction box for securing Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

AMA-A

ADVANCE NEXT CORNER BACKPLATE

Corner-mounting accessory for Next and Advance cameras. For model compatibility please refer to the diagram in the download section.

The technical specifications are subject to change without prior notice.