Thin HDMI Cable

UACC-Cable-UHS

Datasheet Marketing Images

Overview

Length	1, 2, 5 m (3.3, 6.6, 16.4 ft)
Type	HDMI 2.1b
Flame Rating	VW-1 (UL1581)
Weight	18, 45, 85 g (0.6, 1.6, 3 oz)
Unidirectional	1 m: — 2 m: — 5 m: Yes
Cable	
Jacket Diameter	1 m: 2.8 mm (0.11") 2 m: 4 mm (0.16") 5 m: 3.3 mm (0.13")
Jacket Material	1/2 m: Thermoplastic elastomer (TPE) 5 m: Thermoplastic elastomer (TPE), braided

Jacket Color	Black
Conductor Type	1/2 m: Bare copper 5 m: Fiber optics
Conductor Wire Gage	1 m: 38 AWG 2 m: 34 AWG 5 m: —
Bend Radius	1 m: Min. 11.2 mm (0.44") 2 m: Min. 32 mm (1.26 ") 5 m: Min. 26.4 mm (1")
Standards	HDMI 2.1b
Ambient Storage Temperature	1/2 m: -20 to 80°C (-4 to 176°F) 5 m: -20 to 70°C (-4 to 158°F)
Ambient Operating Temperature	1/2 m: -20 to 80°C (-4 to 176°F) 5 m: -20 to 70°C (-4 to 158°F)

Stay in Touch

Email Subscribe

Terms of Service | Privacy Policy | Legal | Cookies Settings

© 2026 Ubiquiti, Inc. All rights reserved.