

DA-LP1101R / DA-LP1101T

Long Reach PoE Extender



DATASHEET

POE INJECTOR / REPEATER FUNCTION

port	RJ45 x1 with PD RJ45 x1 with PSE
connectivity	RJ45, Auto-MDI/MDI-X Sensing
Power Input	IEEE 802.3at, 48 ~ 56V DC
Power Output	Max. 720mA
PoE Standard	IEEE 802.3at PD IEEE 802.3at PSE
PSE Budget	up to 30W
Speed	10/100/1000Mbps

LONG REACH POE EXTENDER FUNCTION

port	RJ45 x1 with PD RJ45 x1 with PSE
connectivity	RJ45, Auto-MDI/MDI-X Sensing
Power Input	IEEE 802.3at, 48 ~ 56V DC

Power Output	Max. 720mA
PoE Budget	Up to 30W(Depending on Cable Distance and Power Input)
cable	UTP CAT5E or Above
Speed	10/100Mbps

LEDS AND BUTTON

Link Status LED	2 Yellow LED(Link/Activity LED per Ethernet port)
PoE Status	1 Green LED(PSE LED)
Reset Button	None
Power LED	1 Green LED

GENERAL

Dimensions (W x H x D)	104 x 34 x 96(mm)
Unit Weight	226g
Operating Temperature	-10℃ ~ 50℃
Operating Humidity	0% ~ 90%
Power Input	56VDC
Power Consumption	56V~, 0.786A, 44W
Approvals	KC, CE, FCC

DIMENSIONS

Unit - mm (inch)

