



TL-R6020Sep-RP

JBOD Connection Interface	SAS
Drive Bay	60 x 3.5-inch The system is shipped without HDD. For the HDD compatibility list, please visit https://www.qnap.com/compatibility/
Drive Compatibility	3.5-inch bays: 3.5-inch SAS 12Gb/s, 6Gb/s hard disk drives 3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives
Hot-swappable	Yes
Form Factor	4U Rackmount
Host Interface	4 x 12Gb/s SAS 3.0 wide ports (4-wide port) Mini-SAS HD (SFF-8644)
LED Indicators	Front panel: HDD 1-60, Power Button, Power Status LED, Power Failure LED, Temperature (Overheating) LED, FAN Fault LED Rear panel: SAS connector, SAS UP/ DOWN Link Status LEDs, ID LED
Buttons	Power
Dimensions (HxWxD)	176 × 482 × 750 mm Excludes ear hook and the protruding part of the Power Supply Unit.
Weight (Net)	25.204 kg
Weight (Gross)	38.5 kg 47.35 kg / 104.45 lbs (with pallet)
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	1300W(x2), 200-240Vac
Power Consumption: Operating Mode, Typical	746.21 W Tested with drives fully populated.

Fan	6 x 120mm, 12VDC
System Warning	Power Failure LED, Temperature (Overheating) LED, FAN Fault LED
QTS / QuTS hero	QuTS hero
Supports JBOD cascading	Yes
Supports expanding NAS storage pools	Yes
Supports Multi-path	Yes
Standard Warranty	5
Management	Managed via QNAP QuTS hero OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure 4. Smart fan control by detecting system and hard drive temperature 5. In-band SAS firmware update

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.