

# Specifications



## Eaton ELSPSTWC

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, white, FIRE, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor

### General specifications

|                         |                                          |
|-------------------------|------------------------------------------|
| <b>PRODUCT NAME</b>     | Eaton Eluxa high fidelity speaker strobe |
| <b>CATALOG NUMBER</b>   | ELSPSTWC                                 |
| <b>UPC</b>              | 786697009679                             |
| <b>PRODUCT HEIGHT</b>   | 3.64 in                                  |
| <b>PRODUCT DIAMETER</b> | 6.2 in                                   |
| <b>PRODUCT WEIGHT</b>   | 1.86 lb                                  |
| <b>COMPLIANCES</b>      | Not Applicable                           |
| <b>PRODUCT TYPE</b>     | High fidelity speaker strobe             |

## Product specifications

|                                 |                             |
|---------------------------------|-----------------------------|
| <b>MOUNTING METHOD</b>          | Ceiling                     |
| <b>HOUSING COLOR</b>            | White                       |
| <b>INDOOR/OUTDOOR</b>           | Indoor                      |
| <b>HOUSING MATERIAL</b>         | Plastic                     |
| <b>LETTERING</b>                | FIRE                        |
| <b>VOLTAGE</b>                  | 24 V<br>25 V<br>70 V        |
| <b>OPERATING TEMPERATURE</b>    | 32°F to 122°F (0°C to 50°C) |
| <b>COMPLIANCE AND STANDARDS</b> | UL<br>ULC<br>FCC            |

## Speaker specifications

|                              |                     |
|------------------------------|---------------------|
| <b>FREQUENCY RANGE - MIN</b> | 300 Hz              |
| <b>FREQUENCY RANGE - MAX</b> | 8000 Hz             |
| <b>SOUND LEVEL (DBA)</b>     | 75/79/82/85/87      |
| <b>TAPS (SELECTABLE)</b>     | 1/8, 1/4, 1/2, 1, 2 |

## Strobe specifications

|                          |                                                                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>LAMP TYPE</b>         | LED                                                                                                                                     |
| <b>CANDELA SETTINGS</b>  | 15 cd<br>30 cd<br>75 cd<br>95 cd<br>150 cd<br>177 cd                                                                                    |
| <b>CURRENT DRAW (DC)</b> | <ul style="list-style-type: none"><li>• 0.022</li><li>• 0.030</li><li>• 0.060</li><li>• 0.086</li><li>• 0.125</li><li>• 0.185</li></ul> |
| <b>LENS COLOR</b>        | Clear                                                                                                                                   |
| <b>LENS MATERIAL</b>     | Lexan                                                                                                                                   |

## Resources

|                                      |                                                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                     | <a href="#">Eluxa family brochure</a><br><a href="#">Eluxa product cross reference</a>                                                         |
| <b>CERTIFICATION REPORTS</b>         | <a href="#">Eluxa indoor speaker devices CSFM listing</a><br><a href="#">Eluxa FM Certificate of Conformity</a>                                |
| <b>COMPLIANCE INFORMATION</b>        | <a href="#">Eluxa UL listing</a>                                                                                                               |
| <b>DRAWINGS</b>                      | <a href="#">Eluxa speaker strobe wall drawing</a><br><a href="#">Eluxa speaker strobe ceiling drawing</a>                                      |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">Installation instructions eluxa horn strobe clear and amber lens ceiling mount</a>                                                 |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - ELSPSTWC</a><br><a href="#">Eluxa high fidelity speaker and speaker strobe data sheet (TD450158EN)</a> |
| <b>TECHNICAL DATA SHEETS</b>         | <a href="#">wheelock-mounting-accessories-data-sheet</a>                                                                                       |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

