

Specifications



Eaton ELSPSTWC-AL

Eaton Eluxa high fidelity speaker strobe, LED, ceiling, white, ALERT, clear lens, 15/30/75/110/150/177 cd, 25/70V, indoor

General specifications

PRODUCT NAME	Eaton Eluxa high fidelity speaker strobe
CATALOG NUMBER	ELSPSTWC-AL
UPC	786697010569
PRODUCT HEIGHT	3.64 in
PRODUCT DIAMETER	6.2 in
PRODUCT WEIGHT	1.86 lb
COMPLIANCES	Not Applicable
PRODUCT TYPE	High fidelity speaker strobe

Product specifications

MOUNTING METHOD	Ceiling
HOUSING COLOR	White
INDOOR/OUTDOOR	Indoor
HOUSING MATERIAL	Plastic
LETTERING	ALERT
VOLTAGE	24 V 25 V 70 V
OPERATING TEMPERATURE	32°F to 122°F (0°C to 50°C)
COMPLIANCE AND STANDARDS	UL ULC FCC

Speaker specifications

FREQUENCY RANGE - MIN	300 Hz
FREQUENCY RANGE - MAX	8000 Hz
SOUND LEVEL (DBA)	75/79/82/85/87
TAPS (SELECTABLE)	1/8, 1/4, 1/2, 1, 2

Strobe specifications

LAMP TYPE	LED
CANDELA SETTINGS	15 cd 30 cd 75 cd 95 cd 150 cd 177 cd
CURRENT DRAW (DC)	• 0.022 • 0.030 • 0.060 • 0.086 • 0.125 • 0.185
LENS COLOR	Clear
LENS MATERIAL	Lexan

Resources

BROCHURES	Eluxa family brochure Eluxa product cross reference
CERTIFICATION REPORTS	Eluxa indoor speaker devices CSFM listing Eluxa FM Certificate of Conformity
COMPLIANCE INFORMATION	Eluxa UL listing
DRAWINGS	Eluxa speaker strobe wall drawing Eluxa speaker strobe ceiling drawing
INSTALLATION INSTRUCTIONS	Installation instructions eluxa horn strobe clear and amber lens ceiling mount
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - ELSPSTWC-AL Eluxa high fidelity speaker and speaker strobe data sheet (TD450158EN)
TECHNICAL DATA SHEETS	wheelock-mounting-accessories-data-sheet

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

