

# Specifications



## Eaton ELSPSTW-N

Eaton Eluxa high fidelity speaker strobe, LED, wall, white, no lettering, clear lens, 15/30/75/110/135/185 cd, 25/70V, indoor

### General specifications

|                             |                                          |
|-----------------------------|------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Eluxa high fidelity speaker strobe |
| <b>CATALOG NUMBER</b>       | ELSPSTW-N                                |
| <b>UPC</b>                  | 786697010446                             |
| <b>PRODUCT LENGTH/DEPTH</b> | 6.35 in                                  |
| <b>PRODUCT HEIGHT</b>       | 2.94 in                                  |
| <b>PRODUCT WIDTH</b>        | 4.56 in                                  |
| <b>PRODUCT WEIGHT</b>       | 1.75 lb                                  |
| <b>COMPLIANCES</b>          | Not Applicable                           |
| <b>PRODUCT TYPE</b>         | High fidelity speaker strobe             |

## Product specifications

|                                 |                             |
|---------------------------------|-----------------------------|
| <b>MOUNTING METHOD</b>          | Wall                        |
| <b>HOUSING COLOR</b>            | White                       |
| <b>INDOOR/OUTDOOR</b>           | Indoor                      |
| <b>HOUSING MATERIAL</b>         | Plastic                     |
| <b>LETTERING</b>                | No lettering                |
| <b>VOLTAGE</b>                  | 24 V<br>25 V<br>70 V        |
| <b>OPERATING TEMPERATURE</b>    | 32°F to 122°F (0°C to 50°C) |
| <b>COMPLIANCE AND STANDARDS</b> | UL<br>ULC<br>FCC            |

## Speaker specifications

|                              |                     |
|------------------------------|---------------------|
| <b>FREQUENCY RANGE - MIN</b> | 300 Hz              |
| <b>FREQUENCY RANGE - MAX</b> | 8000 Hz             |
| <b>SOUND LEVEL (DBA)</b>     | 75/79/82/85/87      |
| <b>TAPS (SELECTABLE)</b>     | 1/8, 1/4, 1/2, 1, 2 |

## Strobe specifications

|                          |                                                                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>LAMP TYPE</b>         | LED                                                                                                                                     |
| <b>CANDELA SETTINGS</b>  | 15 cd<br>30 cd<br>75 cd<br>110 cd<br>135 cd<br>185 cd                                                                                   |
| <b>CURRENT DRAW (DC)</b> | <ul style="list-style-type: none"><li>• 0.022</li><li>• 0.030</li><li>• 0.060</li><li>• 0.086</li><li>• 0.125</li><li>• 0.185</li></ul> |
| <b>LENS COLOR</b>        | Clear                                                                                                                                   |
| <b>LENS MATERIAL</b>     | Lexan                                                                                                                                   |

## Resources

|                                      |                                                                                                                   |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                     | <a href="#">Eluxa family brochure</a><br><a href="#">Eluxa product cross reference</a>                            |
| <b>CERTIFICATION REPORTS</b>         | <a href="#">Eluxa indoor speaker devices CSFM listing</a><br><a href="#">Eluxa FM Certificate of Conformity</a>   |
| <b>COMPLIANCE INFORMATION</b>        | <a href="#">Eluxa UL listing</a>                                                                                  |
| <b>DRAWINGS</b>                      | <a href="#">Eluxa speaker strobe wall drawing</a><br><a href="#">Eluxa speaker strobe ceiling drawing</a>         |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">Eluxa installation instructions speaker strobe p85967a clear amber wall</a>                           |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - ELSPSTW-N</a><br><a href="#">wheelock-mounting-accessories-data-sheet</a> |
| <b>TECHNICAL DATA SHEETS</b>         | <a href="#">Eluxa high fidelity speaker and speaker strobe data sheet (TD450158EN)</a>                            |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

