

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, Colocation, 42U, Black, 1991H x 600W x 1070D mm [TAA]

AR3200

⚠ Discontinued on: Oct 31, 2025

⚠ To be end-of-service on: Sep 19, 2026

⚠ To be discontinued

### Overview

|              |                                                                                                                                                                                                                             |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentation | Two compartment enclosure for colocation facilities with customers requiring a minimal amount of rack space. This multi-tenant, security enhanced enclosure is provided with a compact width to optimize data center space. |
| Lead time    | Usually in Stock                                                                                                                                                                                                            |

### Main

|                           |                                                                                                                                                                                                                              |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or Component Type | Rack enclosure                                                                                                                                                                                                               |
| Number of rack unit       | 42U                                                                                                                                                                                                                          |
| Provided equipment        | 3-Digit Combination Style Handles<br>Adjustable vertical mounting rails<br>Baying hardware<br>Documentation CD<br>Door key<br>Installation guide<br>Leveling feet<br>Pre-installed casters<br>Rack mounting hardware<br>Roof |

### Physical

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Height                     | 78.4 in (1991 mm)                                                                                                                 |
| Width                      | 23.6 in (600 mm)                                                                                                                  |
| Depth                      | 42.1 in (1070 mm)                                                                                                                 |
| Product Weight             | 310.2 lb(US) (140.7 kg)                                                                                                           |
| Color                      | Black                                                                                                                             |
| Mounting preference        | No preference                                                                                                                     |
| Mounting Mode              | Not rack-mountable                                                                                                                |
| Maximum Mounting Depth     | 37.2 in (944.9 mm)                                                                                                                |
| Rack Width                 | 19"                                                                                                                               |
| Marking                    | 14 gauge EIA mounting rail<br>16 gauge front door<br>16 gauge post<br>18 gauge rear door<br>18 gauge roof<br>18 gauge side panels |
| Permanent permissible load | 2250 lb(US) (1020.6 kg) dynamic<br>3750 lb(US) (1701.0 kg) static                                                                 |

### Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|           |            |
|-----------|------------|
| Standards | UL 2416    |
|           | UL 60950-1 |
|           | EIA-310E   |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304284130 |
|------|--------------|

## Packing Units

|                        |                           |
|------------------------|---------------------------|
| Unit Type of Package 1 | PCE                       |
| Nbr. of units in pkg.  | 1                         |
| Package 1 Height       | 83.3 in (211.7 cm)        |
| Package 1 Width        | 29.4 in (74.6 cm)         |
| Package 1 Length       | 45.5 in (115.6 cm)        |
| Package weight(Lbs)    | 371.15 lb(US) (168.35 kg) |

## Compliance

|            |                        |
|------------|------------------------|
| Compliance | TAA Compliant          |
|            | BAA Compliant via COTS |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 60 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 591 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 564 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 14 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 0 kg CO2 eq.                                  |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 13 kg CO2 eq.                                 |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------|
| Packaging made with recycled cardboard | No                                                                          |
| Packaging without single use plastic   | No                                                                          |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 95                                                                                                                                                                                                               |
| Circularity Profile           | No need of specific recycling operations                                                                                                                                                                         |
| Take-back                     | No                                                                                                                                                                                                               |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

Alternative

---







