

HFCD1 Series Indoor Tight Buffer
Distribution, 2 strand, Plenum, OM4, MM,
Aqua Jacket

By Hubbell Premise Wiring
Catalog # [HFCD1002P4](#)

HFCD1 Series Indoor Tight Buffer Distribution, 2 strand, Plenum,
OM4, MM , Aqua Jacket

Features

- Multimode Bend-Insensitive Optical Fiber
- E-Z Strip Buffer For Contractor-Friendly Termination
- Compact Cable Diameter Reduces Pathway Congestion
- Premium Fiber For Enhanced Optical Performance

Application

Data Transmission

Specifications

Industry Standard(s)TIA

Conductor

Fiber SizeOM4
Fiber TypeOM4, MM
Number Of Fibers2

Current

Wavelength850/1300 Nanometers

General

Sub BrandFiber Optics

Type

Cable Rating
Material - Jacket
Specifications

Cable

Plenum
PVC

- Armor - None
- Cable Diameter in (mm) - 0.17 (4.4)
- Cable Weight (lb/kft) - 12
- Construction - Single Unit, Aramid Strength Member
- Fiber Coating - 900 Micron PVC Tight Buffer

662620555461
Aqua

Operational

Attenuation3.5/1.5 Db per Kilometer
Temperature Rating0 Degrees C to 70 Degrees C
Bandwidth4000 bps

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)

