

MW-42BT-AM

AUDIO INTERFACE WITH USB AND BLUETOOTH



Equipped with Bluetooth®, USB, auxiliary input, and a line/microphone input. The in-wall design and timeless appearance make the MW-42BT easily integrate with any environment and save space.

Key features

Specifications

Power Source	100-240V AC 50/60Hz
Current Consumption	3W
Attenuation	LINE/MIC input: -10 dBV, 10 k Ω /-60 dBV, 600 Ω , electronic balanced, female XLR Connector AUX input: -10 dBV, 10 k Ω , unbalanced, stereo 3.5 mm(1/8") mini jack USB inputL Audio formats: MP3, WAV — Format: FAT16, FAT32, Max. 32GB Bluetooth® input: Ver 5.4, Max 10m
Control	Stereo/Monaural output, 0 dBV, 10 k Ω , electronic balanced, removable terminal block
Indicator	Power (Blue) x1, LINE/MIC (Blue) x1, AUX (Blue) x1, USB (Blue) x1, Bluetooth® (Blue) x1
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	90% RH or less (no condensation)
Finish	Panel: Aluminum, Sandblasting, Silver Decorative Sheet: Acrylic, Black
Dimensions	120 (W) x 120 (H) x 40.2 (D) mm (4.72" x 4.72" x 1.58")
Weight	0.2 kg (0.44lbs)
Included Accessories	AC Power adapter x1, Remote control x1, Box mounting screw (6-32UNC) x4, Grounding screw x1, Flat gasket x2, Fixed gasket x1, Removable terminal plug (8 pins) x1

Dimensions

■ APPEARANCE

