

Technical Specifications

VM-SRLY Smart Relay for SIP Door Intercoms

- Smart signaling reduces possibility of tampering
- 1 Form C relay
- Compatible with Valcom's VIP-176A



VIP-176A compatible

Description:

The VM-SRLY Smart Relay module is designed for use with the VIP-176A IP Doorphone/Intercom.

SPECIFICATIONS

ACCESS METHODS

Valcom SIP Intercoms

AUXILIARY RELAYS

Form C Relay rated 1A @ 24 Vdc

ENVIRONMENT

Temperature: +32 to +104 °F (0 to +40 °C)

Humidity: 0 to 85% non-precipitating

DIMENSIONS AND WEIGHT

2.50in H x 1.25in W x 1.25in D
(6.40cm x 3.20cm x 3.20cm)

Weight: 0.06lbs (0.03kg)

Shipping Weight: 2.20lbs (0.99kg)

MOUNTING

Mount to a solid surface

COMPATIBILITY

VIP-176A Doorphone/Intercom

ARCHITECTS AND ENGINEERS

The Smart Relay Module, model VM-SRLY, shall be designed for use with Valcom SIP Intercoms. The Smart Relay shall provide both a normally open and normally closed (Form C) output connection for use with auxiliary equipment such as electric door strikes, gate openers, etc. The VM-SRLY shall be compatible with the VIP-176A SIP Doorphone/Intercom.

The power and signal connections shall be provided to the VM-SRLY by a four wire connector. The recommended wiring uses two pairs from a standard Category 3 (or better) twisted-pair cable.

The VM-SRLY Smart Relay Module shall be mounted to a solid surface using the double-sided tape affixed to the back of the module or using the #4 x 0.75in screws included.

Maximum dimensions shall be: 2.50in H x 1.25in W x 1.25in D (6.40cm x 3.20cm x 3.20cm). Weight shall be approximately 0.06lbs (0.03kg).

Warranty information may be found on our website at www.valcom.com/warranty.

2022 Rev. 1.6.2.4



SALES@VALCOM.COM

800.825.2661

VALCOM.COM