



2026 Edge Devices Accessory Guide



© 2026 Teledyne FLIR LLC All rights reserved worldwide. No parts of this manual, in whole or in part, may be copied, photocopied, translated, or transmitted to any electronic medium or machine readable form without the prior written permission of Teledyne FLIR LLC.

Names and marks appearing on the products herein are either registered trademarks or trademarks of Teledyne FLIR LLC and/or its subsidiaries. All other trademarks, trade names, or company names referenced herein are used for identification only and are the property of their respective owners.

This product is protected by patents, design patents, patents pending, or design patents pending. Photographs and images appearing in this manual may have been modified for illustrative purposes using commercial image editing software and may not always reflect an actual product configuration.

The contents of this document are subject to change without notice.
For additional information visit www.flir.com or write to Teledyne FLIR LLC

Teledyne FLIR LLC
Antennvägen 6
PO Box 7376
SE-187 15 Täby Stockholm County
187 66
Sweden
Support: <https://support.flir.com/>

Document History

Revision	Date	Comment
100	January 2026	Initial 2026 release.
110	March 2026	Added hemispheric camera, other minor edits.
120	April 2026	Added new CM-350x accessories, added PT-Series AI wall mount and adapter plate dependency, fixed CM-320x accessories, minor fixes.
130	June 2026	Added PF-NPT adapter clarification to DX accessories, edited CM-640x accessories.

Contents

1. Introduction	4
2. Product Registration and Warranty Information	5
3. Thermal Cameras	6
3.1 FLIR FCB-Series AI.....	7
3.2 FLIR ELARA™ FB-SERIES ID.....	9
3.3 FLIR FH-Series ID	10
3.3.1 Raytec™ Products.....	13
3.4 FLIR FH-Series R	14
3.4.1 Raytec™ Products.....	17
3.5 FLIR FC-Series AI/AI-R.....	18
3.6 FLIR TRITON™ F-Series ID.....	20
3.7 FLIR PT-Series AI SR.....	22
3.8 FLIR ELARA™ DX-Series	24
4. Visible Cameras.....	27
4.1 FLIR QUASAR™ Premium 1080p IR PTZ (CP-6402-41-IA)	28
4.2 FLIR QUASAR™ Premium 1080p Pendant PTZ (CP-640x-xx-AI)	31
4.3 FLIR QUASAR™ FHD Dome Indoor Recessed PTZ (CP-6402-30-RA).....	34
4.4 FLIR QUASAR™ Premium 4K IR PTZ (CP-6408-xx-IA).....	35
4.5 FLIR QUASAR™ 4K IR PTZ Cameras (CP-6408-xx-I)	38
4.6 FLIR ARIEL™ 4K UHD Mini-Dome (CM-3304-xx-I).....	41
4.7 FLIR ARIEL™ HD Mini-Dome (CM-320x)	44
4.8 FLIR ARIEL™ Mini-Dome (CM-350x)	46
4.9 FLIR ARIEL™ Corner Camera (CC-3405-01-I & CC-3408-01-AI).....	50
4.10 FLIR QUASAR™ 4 x 2K Panoramic Camera (CM-6308)	51
4.11 FLIR QUASAR™ Hemispheric Mini-Dome AI (CM-6412-H2-AI)	52
4.12 FLIR QUASAR™ Premium Mini-Dome (CM-640x).....	54
4.13 FLIR QUASAR™ Premium Mini-Dome AI (CM-640x-xx-AI)	57
4.14 FLIR QUASAR™ Premium Bullet AI (CB-650x-x1-AI)	60
4.15 FLIR QUASAR™ Premium Fixed Box AI (CF-6408)	62
4.16 FLIR QUASAR™ 4K Fixed Box (CF-6308)	63
5. Radar.....	65
5.1 FLIR ELARA™ R-SERIES RADAR	66
6. Disclaimer	68

1. Introduction

Welcome to the FLIR Security Accessories Catalogue, your comprehensive resource for selecting the optimal accessories to complement and enhance your FLIR Security Edge devices. Whether you are specifying mounting solutions, exploring compatible power accessories, or seeking to optimize camera performance, this guide is designed to help you navigate the full range of options available.

To ensure you have access to the most current information, features, and updates, we strongly recommend downloading the latest version of this catalogue [here](#). Staying up to date will help you make the best selections and avoid outdated specifications or product details.

2. Product Registration and Warranty Information


Register your Product with Teledyne FLIR at <https://customer.flir.com>.

For warranty information, see <https://www.teledyneflir.com/support-center/warranty/security/flir-security-product-warranties/>.

3. Thermal Cameras

3.1 FLIR FCB-Series AI



Part number / item code	Description	Images
CM-SECA-W4	Side conduit adapter kit, with cable housing attached: • Replaces mounting bracket included in the camera kit. • Attaches to standard electrical box or directly to mounting surface. • Dimensions: 191 x 157 x 52 mm. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 2.83 kg.	
CM-4S-32	4S electrical box mount adapter plate: • For outdoor applications. • Can be used with DH-Series pendant mount accessories. • Dimensions: 142 (D) x 5 (H) mm. • Color: FLIR White.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	

CX-POLE-G32	Pole mount kit, including straps, for use with CM-CAPX-W32 wall mount with pendant cap kit: • Dimensions: 240 x 180 x 60 mm. • Pole diameter range: 130~152 mm. • Color: Cool Gray 2C.	
CB-BKBX-65	Back Box with 3/4" (20 mm) NPT conduit holes: • Included in the box with the camera. • Dual-hole, back and side.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

3.2 FLIR ELARA™ FB-SERIES ID



Part number / item code	Description	Images
CB-WLBX-62	Wall junction box mount kit: • IP66 cable management box. • Heavy-duty aluminum with 1/2" conduit connection. • Shipping box size: 17.3 x 17.3 x 10.7 cm. • Shipping box weight: 0.84 kg.	
CB-PLBX-62	Pole junction box mount kit, including straps: • IP66 cable management box with 1/2" conduit connection. • Pole diameter range $\varnothing$ 64-216 mm (2 1/2-8 1/2"). • Junction box material: Heavy-duty aluminum. • Strap, housing, and screw: Stainless steel. • Shipping box size: 17.3 x 17.3 x 16.7 cm. • Shipping box weight: 1.03 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

3.3 FLIR FH-Series ID



Part number / item code	Description	Images
421-0086-00	Illuminator mount bracket for FH-Series cameras: • Dimensions: 123 x 40 x 110 mm. • Color: Black. • Shipping box size: 178 x 165 x 140 mm (7 x 6.5 x 5.5 in). • Shipping box weight: 0.66 kg (1.45 lbs.).	
421-0087-00	Wall mount assembly for FH-Series cameras: • Dimensions: 373.42 x 148 x 174.53 mm. • Weight: 1.3 kg (2.87 lbs.). • Color: White. • Material: Aluminum. • Shipping box size: 420 x 180 x 130 mm (16.5 x 7 x 5 in). • Shipping box weight: 2.15 kg (4.75 lbs.).	
500-1120-00	Pedestal mount assembly for F-Series and FH Series cameras: • Dimensions (H x W): 328 mm (12.9") x 216 mm (8.5"). • Color: FLIR White.	
500-1119-00	Corner mount kit: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly.	

500-1121-00	Small pole mount kit: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 500-1110-00 FH-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 4129742 FC-Series concealed cable wall mount. • Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8"). • Pole diameter range: 65-110 mm (2.6-4.3"). • Color: FLIR White.	
500-1116-00	Large pole mount kit, including straps: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 500-1110-00 PT-Series wall mount assembly. • Pole diameter range: 150-230 mm (6-9"). • Color: FLIR White.	
4124857	UL listed and approved 300 W 24 VAC power supply: • Ratings: NEMA 4X weather-resistant enclosure. • Input: 115 VAC 60 Hz @ 3 A, or 230 VAC 50 Hz @ 1.5 A. • Output: 24 VAC @ 12.5 A, or 28 VAC @ 10 A. • Fuse rating: 10 A / 32 V. • Safety: UL / CUL.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	

T912483

90 W Single Port Multi-Gig PoE++ Injector:

- IEEE802.3bt Compliant.
- 4 Pair Powering +3,6,4,5 / - 1,2,7,8.
- Full Protection OCP, OVP.
- Broken Wire Detection.
- Gigabit Compatible
- Shielded DC Jacks.
- UL/cUL 60950-1; UL/cUL 62368-1; AS/NZ 623682; IEC60950-1; IEC62368-1; CE.
- Dimensions: 166 mm (6.53 in) x 44 mm (1.73 in) x 80 mm (3.15 in).
- Weight: 500 g (1.1 lbs.).



3.3.1 Raytec™ Products

Please note that Teledyne FLIR doesn't sell nor distribute Raytec products. They are listed here for informational purposes only.

FH Series Model	Illuminator model	Angles	Lens model	Distances	Images
FH-369	VAR2-i6-1	120 x 50°	VAR-i6-LENS-12050 (Optional)	30 m (98 ft)	
FH-324		35 x 10°	Fitted as standard	100 m (394 ft)	
FH-669	VAR2-i6-2	60 x 25° per panel	Included	Narrow: 99 m (325 ft) at 60° Wide: 70 m (230 ft) at 120°	
FH-313	VAR2-i8-1	35 x 10°	Fitted as standard	165 m (541 ft)	
FH-625		60 x 25°	Included	95 m (311 ft)	
FH-644	VAR2-i8-2	10 x 10° per panel	Included	Narrow: 500 m (1640 ft) at 10° Wide: 354 m (1161 ft) at 20°	
FH-612	VAR2-i16-1	35 x 10°	Fitted as standard	250 m (820 ft)	
FH-617		10 x 10°	Included	500 m (1640 ft)	
FH-610					
FH-608					

3.4 FLIR FH-Series R



Part number / item code	Description	Images
421-0086-00	Illuminator mount bracket for FH-Series cameras: • Dimensions: 123 x 40 x 110 mm. • Color: Black. • Shipping box size: 178 x 165 x 140 mm (7 x 6.5 x 5.5 in). • Shipping box weight: 0.66 kg (1.45 lbs.).	
421-0087-00	Wall mount assembly for FH-Series cameras: • Dimensions: 373.42 x 148 x 174.53 mm. • Weight: 1.3 kg (2.87 lbs.). • Color: White. • Material: Aluminum. • Shipping box size: 420 x 180 x 130 mm (16.5 x 7 x 5 in). • Shipping box weight: 2.15 kg (4.75 lbs.).	
500-1120-00	Pedestal mount assembly for F-Series and FH Series cameras: • Dimensions (H x W): 328 mm (12.9") x 216 mm (8.5"). • Color: FLIR White.	
500-1119-00	Corner mount kit for use with: • 500-1123-00 F-Series wall mount assembly. • 421-0087-00 FH-Series wall mount assembly.	

500-1121-00	Small pole mount kit: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 500-1110-00 FH-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 4129742 FC-Series concealed cable wall mount. • Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8"). • Pole diameter range: 65-110 mm (2.6-4.3"). • Color: FLIR White.	
500-1116-00	Large pole mount kit, including straps: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 500-1110-00 PT-Series wall mount assembly. • Pole diameter range: 150-230 mm (6-9"). • Color: FLIR White.	
4124857	UL listed and approved 300 W 24 VAC power supply: • Ratings: NEMA 4x weather-resistant enclosure. • Input: 115 VAC 60 Hz @ 3 A, or 230 VAC 50 Hz @ 1.5 A. • Output: 24 VAC @ 12.5 A, or 28 VAC @ 10 A. • Fuse rating: 10 A / 32 V. • Safety: UL / CUL.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	

T912483

90 W Single Port Multi-Gig PoE++ Injector:

- IEEE802.3bt Compliant.
- 4 Pair Powering +3,6,4,5 / - 1,2,7,8.
- Full Protection OCP, OVP.
- Broken Wire Detection.
- Gigabit Compatible
- Shielded DC Jacks.
- UL/cUL 60950-1; UL/cUL 62368-1; AS/NZ 623682; IEC60950-1; IEC62368-1; CE.
- Dimensions: 166 mm (6.53 in) x 44 mm (1.73 in) x 80 mm (3.15 in).
- Weight: 500 g (1.1 lbs.).



3.4.1 Raytec™ Products

Please note that Teledyne FLIR doesn't sell nor distribute Raytec products. They are listed here for informational purposes only.

FH Series Model	Illuminator model	Angles	Lens model	Distances	Images
FH-369	VAR2-i6-1	120 x 50°	VAR-i6-LENS-12050 (Optional)	30 m (98 ft)	
FH-324		35 x 10°	Fitted as standard	100 m (394 ft)	
FH-669	VAR2-i6-2	60 x 25° per panel	Included	Narrow: 99 m (325 ft) at 60° Wide: 70 m (230 ft) at 120°	
FH-313	VAR2-i8-1	35 x 10°	Fitted as standard	165 m (541 ft)	
FH-625					
FH-644		60 x 25°	Included	95 m (311 ft)	
FH-612	VAR2-i8-2	10 x 10° per panel	Included	Narrow: 500 m (1640 ft) at 10° Wide: 354 m (1161 ft) at 20°	
FH-617	VAR2-i16-1	35 x 10°	Fitted as standard	250 m (820 ft)	
FH-610					
FH-608		10 x 10°	Included	500 m (1640 ft)	

3.5 FLIR FC-Series AI/AI-R



Part number / item code	Description	Images
4129742	Concealed cable wall mount: • Can be used with other F-, FH-, FC-, and PT-Series mounting accessories.	
421-0087-00	Wall mount assembly for FH-Series cameras: • Dimensions: 373.42 x 148 x 174.53 mm. • Weight: 1.3 kg (2.87 lbs.). • Color: White. • Material: Aluminum. • Shipping box size: 420 x 180 x 130 mm (16.5 x 7 x 5 in). • Shipping box weight: 2.15 kg (4.75 lbs.).	
4132982	Large pole mount kit for use with 4129742 wall mount assembly: • Concealed cables. • Pole diameter range: 75-180 mm (3-7"). • Bracket material: Aluminum. • Bracket finish: Clear hard-coated anodize.	
500-1121-00	Small pole mount kit: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 500-1110-00 FH-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 4129742 FC-Series concealed cable wall mount. • Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8"). • Pole diameter range: 65-110 mm (2.6-4.3"). • Color: FLIR White.	

500-1119-00	Corner mount kit for use with: • 500-1123-00 F-Series wall mount assembly. • 421-0087-00 FH-Series wall mount assembly.	
4124857	UL listed and approved 300 W 24 VAC power supply: • Ratings: NEMA 4x weather-resistant enclosure. • Input: 115 VAC 60 Hz @ 3 A, or 230 VAC 50 Hz @ 1.5 A. • Output: 24 VAC @ 12.5 A, or 28 VAC @ 10 A. • Fuse rating: 10 A / 32 V. • Safety: UL / CUL.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	
T912483	90 W Single Port Multi-Gig PoE++ Injector: • IEEE802.3bt Compliant. • 4 Pair Powering +3,6,4,5 / - 1,2,7,8. • Full Protection OCP, OVP. • Broken Wire Detection. • Gigabit Compatible • Shielded DC Jacks. • UL/cUL 60950-1; UL/cUL 62368-1; AS/NZ 623682; IEC60950-1; IEC62368-1; CE. • Dimensions: 166 mm (6.53 in) x 44 mm (1.73 in) x 80 mm (3.15 in). • Weight: 500 g (1.1 lbs).	

3.6 FLIR TRITON™ F-Series ID




Part number / item code	Description	Images
4129742	Concealed cable wall mount: Can be used with other F-, FH-, FC-, and PT-Series mounting accessories.	
500-1123-00	Wall mount assembly: Can be used with other F-, FH-, FC-, and PT-Series mounting accessories.	
500-1120-00	Pedestal mount assembly for F-Series and FH Series cameras: - Dimensions (H x W): 328 mm (12.9") x 216 mm (8.5"). - Color: FLIR White.	
500-1119-00	Corner mount kit for use with: 500-1123-00 F-Series wall mount assembly. 421-0087-00 FH-Series wall mount assembly.	
500-1121-00	Small pole mount kit. - For use with: 500-1123-00 F-Series wall mount assembly. 500-1110-00 FH-Series wall mount assembly. 421-0087-00 FH-Series wall mount assembly. 4129742 FC-Series concealed cable wall mount. - Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8"). - Pole diameter range: 65-110 mm (2.6-4.3"). - Color: FLIR White.	

500-1116-00


Small pole mount kit.

- For use with:
 - 500-1123-00 F-Series wall mount assembly.
 - 421-0087-00 FH-Series wall mount assembly.
 - 4129742 FC-Series concealed cable wall mount.
- Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8").
- Pole diameter range: 65-110 mm (2.6-4.3").
- Color: FLIR White.



3.7 FLIR PT-Series AI SR





Part number / item code	Description	Images
500-1110-00	Wall mount assembly: • Can be used with other F-, FH-, FC-, and PT-Series mounting accessories. • Includes adapter plate, wall mount bracket, adapter pluck and screws and washers.	
4119468	PT Series Adapter Plate: • Required for several mounting accessories, including wall and pole mounts. Please, contact customer support or your sale representative for more details.	
500-1118-00	Corner mount kit for use with 500-1110-00 wall mount assembly.	
500-1117-00	Pedestal mount assembly for PT Series cameras: • Dimensions (base): 215.90 mm (8.5"). • Color: FLIR White.	

500-1116-00	Large pole mount kit, including straps: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 500-1110-00 PT-Series wall mount assembly. • Pole diameter range: 150-230 mm (6-9"). • Color: FLIR White.	
500-1121-00	Small pole mount kit: • For use with: ○ 500-1123-00 F-Series wall mount assembly. ○ 500-1110-00 FH-Series wall mount assembly. ○ 421-0087-00 FH-Series wall mount assembly. ○ 4129742 FC-Series concealed cable wall mount. • Dimensions: (H x W) 115 x 173 mm (4.5 x 6.8"). • Pole diameter range: 65-110 mm (2.6-4.3"). • Color: FLIR White.	
PSU-24VDC-10A	Outdoor Power supply: • Input: 220 VAC 50/60 Hz @ 2.5 A (working range 198 VAC – 256 VAC). • Output: 24 VDC @ 10 A. • Other: Short circuit and thermal overload protection, filtered and regulated. • Dimensions: 13.31" x 11.31" x 5.59" (338.1 mm x 287.3 mm x 142 mm). • NEMA 4/4X, IP66-11 rated. • Weight (approx.): 9.2 lb. (5.19 kg) (Product). • Temperature: Operating: – 40 °C to 60 °C (– 40° C to 140 °F), Storage: – 40 °C to 70 °C (– 40 °C to 158 °F). • Relative Humidity: 85% +/- 5%. • BTU/Hr. (approx.): 123 BTU/Hr.	
324-0005-00	PT Series Hard Case with Foam: • Intended for product demonstration purposes.	

3.8 FLIR ELARA™ DX-Series



Part number / item code	Description	Images
FMS00003238	PF-NPT adapter. *Please note: Starting in 2021, DX-Series units are supplied with a 1.5" PF outer thread pendant cap. Units shipped prior to 2021 were equipped with an NPT thread and may require a PF-NPT adapter for compatibility with certain accessories.	
CX-ARMX-G3	Wall mount (1.5" PF inner thread) • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with FMS00003238. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Dimensions 515 x 256 x 1043 mm. • Color White. • Shipping box size 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	

CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Can be used with FMS00003238. • Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Unit weight 12.29 kg (27.09 lbs.). • Color White. • Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	


CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	

4. Visible Cameras

4.1 FLIR QUASAR™ Premium 1080p IR PTZ (CP-6402-41-IA)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions 515 x 256 x 1043 mm. • Color White. • Shipping box size 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	


CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Can be used with FMS00003238. • Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Unit weight 12.29 kg (27.09 lbs.). • Color White. • Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
FMS00003238	PF-NPT adapter: • Provided as part of the CP-640x-xx-AI camera package.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	

CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	

4.2 FLIR QUASAR™ Premium 1080p Pendant PTZ (CP-640x-xx-AI)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Can be used with FMS00003238. • Unit weight 12.29 kg (27.09 lbs.). • Color White. • Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	

CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
FMS00003238	PF-NPT adapter: • Provided as part of the CP-640x-xx-AI camera package.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	

CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
CP-63CLEAR-P	Clear bubble for CP-6302-31-P pendant PTZ camera: • Dimensions: 193 x 127.7 (max) mm. • Color: FLIR White. • Shipping box size: 260 x 255 x 170 mm. • Shipping box weight: 0.60 kg.	
CP-63SMOKE-P	Smoked bubble for CP-6302-31-P pendant PTZ camera: • Dimensions: 193 x 127.7 (max) mm. • Color: FLIR White. • Shipping box size: 260 x 255 x 170 mm. • Shipping box weight: 0.60 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.3 FLIR QUASAR™ FHD Dome Indoor Recessed PTZ (CP-6402-30-RA)




Part number / item code	Description	Images
CP-63CLEAR-R	Clear bubble for CP-6302-30-R recessed PTZ camera: • Dimensions: 212.4 x 102 mm. • Color: FLIR White (with logo printing). • Shipping box size: 260 x 255 x 170 mm. • Shipping box weight: 0.55 kg.	
CP-63SMOKE-R	Clear bubble for CP-6302-30-R recessed PTZ camera: • Dimensions: 212.4 x 102 mm. • Color: FLIR White (with logo printing). • Shipping box size: 260 x 255 x 170 mm. • Shipping box weight: 0.55 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.4 FLIR QUASAR™ Premium 4K IR PTZ (CP-6408-xx-IA)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Can be used with FMS00003238. • Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Unit weight 12.29 kg (27.09 lbs.). • Color White. • Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	


CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
FMS00003238	PF-NPT adapter: • Provided as part of the CP-640x-xx-AI camera package.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	

CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.5 FLIR QUASAR™ 4K IR PTZ Cameras (CP-6408-xx-I)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions 515 x 256 x 1043 mm. • Color White. • Shipping box size 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	


CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Unit dimensions: 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Can be used with FMS00003238. • Unit weight: 12.29 kg (27.09 lbs.). • Color: White. • Shipping box size: 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
FMS00003238	PF-NPT adapter.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	

CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	
CP-POE-4P-60WUS Microsemi products: PD-9501GC/AC PD-9501GR/AC	Inline 60 W over 4 pairs Power over Ethernet (PoE++) injectors: • Support FLIR Security devices that can be powered by PoE++. • PD-9501GC/AC: IEEE 802.3bt-compliant. • PD-9501GR/AC: IEEE 802.3at-compliant. • Teledyne FLIR CP-POE-4P-60W-US is the Microsemi PD-9501GC/AC-US. Other Microsemi power cord options: -EU (Europe), -UK, -BR (Brazil), -AU (Australia), -JP (Japan). • 100-240 VAC input.	

4.6 FLIR ARIEL™ 4K UHD Mini-Dome (CM-3304-xx-I)




Part number / item code	Description	Images
CM-CAPX-31	Pendant cap with 1.5" PF outer thread: - Indoor or outdoor applications. 0.75" female EMT conduit connection. - Can be used with CX-xxxx-G3, -G32, and others. 1.5" PF inner thread mounting hardware.	
CX-ARMX-G3	Wall mount (1.5" PF inner thread): - Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. - Can be used with FMS00003238. - Dimensions: 249 (L) x 140 (W) x 227 (H) mm. - Color: White. - Shipping box size: 29 x 16 x 21 cm. - Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: - Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. - Can be used with FMS00003238. - Dimensions: 316 (L) x 185 (W) x 228(H) mm. - Color: White. - Shipping box size: 29.5 x 21.5 x 22 cm. - Shipping box weight: 3.1 kg.	
CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): - Can be used with FMS00003238. - Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). - Unit weight 12.29 kg (27.09 lbs.). - Color White. - Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	

CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	
FMS00003238	PF-NPT adapter.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	
CM-4S-31	4S electrical box mount adapter plate: • For indoor or weather-protected applications. • Note: All CM-33xx cameras can directly mount to standard round electrical boxes without additional accessories.	

CM-BKBX-31	Conduit back box for CM-330x mini-dome cameras: • Ideal for indoor/outdoor & corrections applications. • Heavy-duty aluminum vandal mount. • IP67 & IK10 ratings. • 0.75" conduit connection. • Dimensions 147.9 x 147.9 x 58.2 mm. • Color FLIR White.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
CM-RCSD-G2	Recessed mounting kit for CM-330x mini-dome cameras, including peel & stick template: • Top mounted 4S electrical box attachment points. • Supports conduit connections. • Maximum surface thickness: 42 mm (1.75"). • Color: White.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3 and CX-ARMX-G3 wall mount kits; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	

4.7 FLIR ARIEL™ HD Mini-Dome (CM-320x)



Part number / item code	Description	Images
CM-4S-32	4S electrical box mount adapter plate: • For outdoor applications. • Adapts CM-3202 cameras to standard 4S electrical box mounting.	
CM-RCSD-G2A	Recessed mounting kit for CM-3202 mini-dome camera, including mounting template guide sticker, trim ring, and CM-4S-32 adapter plate: • Dimensions: 223 (D) x 7.3 (H) mm. • Color: FLIR White.	
CM-WLBX-42	Wall & surface mount kit with junction box for CM-3202 mini-dome camera: • Heavy-duty aluminum mount.	
CM-CAPX-W32	Pendant cap and wall mount kit, including mounting arm and pendant cap, for CB-640x bullet camera and for CM-3202 mini-dome camera: • Minimum wall thickness: 50 mm (2"). • Can be used with CX-POLE-G32 pole mount kit. • Dimensions: 244 x 152 x 142 mm. • Color: FLIR White.	


CX-POLE-G32	Pole mount kit, including straps, for use with CM-CAPX-W32 wall mount with pendant cap kit: • Dimensions: 240 x 180 x 60 mm. • Pole diameter range: 130~152 mm. • Color: Cool Gray 2C.	
CM-CLEAR-32-11	Clear bubble for CM-3202 mini-dome camera: • Dimensions: 124 (D) x 99 (H) mm. • Color: FLIR White.	
CM-SMOKE-32-11	Smoked bubble for CM-3202 mini-dome camera: • Dimensions: 124 (D) x 99 (H) mm. • Color: FLIR White.	

4.8 FLIR ARIEL™ Mini-Dome (CM-350x)



Part number / item code	Description	Images
FMS00005391	Recessed mount kit, Including: • Recessed kit base. • Recessed kit cover.	
FMS00005395	Pole mount kit, including: • Pole shroud. • Pole cover. • Pole adapter plate. • Pole gasket cover. • Silicone gasket. • Safety wire.	
421-0068-00 DH-PDST-00	Pendant mount shroud with 1.5" PF outer thread: • Requires CM-4S-32 adapter plate. • Can be used with CX-xxxx-G3, -G32, and other 1.5" PF inner thread mounting hardware.	
CM-4S-32	4S electrical box mount adapter plate: • For outdoor applications. • Can be used with DH-Series pendant mount accessories. • Dimensions: 142 (D) x 5 (H) mm. • Color: FLIR White.	

CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-XTND-G3	Extendable gooseneck mount kit with cable box and wall mount plate (1.5" PF inner thread): • Can be used with FMS00003238. • Unit dimensions 900-1140 (L) x 256 (W) x 975 (H) mm (35.43-44.88 x 10.08 x 38.39"). • Unit weight 12.29 kg (27.09 lbs.). • Color White. • Shipping box size 89 x 54 x 15.5 cm (35.04 x 21.26 x 6.10").	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
CX-GSNK-G32	Gooseneck mount kit, including base plate and pipe (1.5" PF inner thread): • Can be used with CX-GSNK-G32-B mounting bracket. • Can be used with FMS00003238. • Dimensions: 113 x 838 (L) x 450 (W) mm. • Weight: 5.56 kg. • Color: White. • Shipping box size: 89 x 54 x 13 cm. • Shipping box weight: 6.5 kg.	

FMS00003238	PF-NPT adapter.	
CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-PIPE-G325	50 cm long extender pipe (1.5 PF outer & inner threads): • Dimensions: 54 X 520 mm. • Weight: 1.6 kg. • Color: White. • Shipping box size: 55 x 6.5 x 6.5 cm. • Shipping box weight: 1.66 kg.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
421-0083-00	180° dual-unit wall mount kit:	

4210755


FC-PWR-00


Inline 30 W IEEE 802.3at PoE+ injector:

- Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at.
- 100-240 VAC input.



4.9 FLIR ARIEL™ Corner Camera (CC-3405-01-I & CC-3408-01-AI)



Part number / item code	Description	Images
CC-BKBX-34	Back box for CC-340x corner cameras: • Supports conduit connections. • Dimensions: 147.97 x 158.22 x 36.76 mm (5.83 x 6.23 x 1.45"). • Shipping box size: 15.0 x 14.0 x 4.0 cm. • Shipping box weight: 1 kg.	
CC-COVR-34	Replacement for broken or scratched CC- 3405 camera front cover: • Dimensions: 165 x 154.16 mm (6.50 x 6.07"). • Color: FLIR White.	

4.10 Flir QUASAR™ 4 x 2K Panoramic Camera (CM-6308)



Part number / item code	Description	Images
CM-CAPX-63P	Pendant cap with 1.5" PF outer thread: • Heavy-duty aluminum vandal mount • Ideal for indoor / outdoor & corrections applications • 0.75" conduit connection • Can use with CX-xxxx-G3, -G32, and other 1.5" PF inner thread mounting hardware	
CM-IMG5-63P	5th imager.	

4.11 FLIR QUASAR™ Hemispheric Mini-Dome AI (CM-6412-H2-AI)



Part number / item code	Description	Images
CM-RCSD-G4-F	Recessed mount kit, including ceiling sticker and trim ring.	 Mounted with camera
CX-ARMX-G4-F	Wall mount bracket: For indoor use only. For outdoor applications see CM-CAPX-G4-F.	
CM-CAPX-G4-F	Pendant cap kit, including 1.5" PF outer thread adapter: - For outdoor use. - Can be used with CX-xxxx-G3, -G32, and other 1.5" PF inner thread mounting hardware.	 Mounted with camera
CM-4S-G4-F	Electrical box mount adapter plate.	

4210755

FC-PWR-00

Inline 30 W IEEE 802.3at PoE+ injector:


- Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at.
- 100-240 VAC input.



4.12 FLIR QUASAR™ Premium Mini-Dome (CM-640x)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
FMS00003238	PF-NPT adapter:	



CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
CM-SECA-W4	Side conduit adapter kit, with cable housing attached: • Replaces mounting bracket included in the camera kit. • Attaches to standard electrical box or directly to mounting surface. • Dimensions: 191 x 157 x 52 mm. • Color: Grey. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 2.83 kg.	
CM-RCSD-G4	Recessed mount kit for CM-640x mini-dome cameras, including ceiling sticker template and trim ring: • Supports conduit connections. • Dimensions: 212 x 212 x 76 mm. • Trim ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 1.11 kg.	 Mounted with camera


CM-SNSHLD-G4	Sunshield for CM-640x mini-dome cameras: • Dimensions: 175.68 x 200.51 x 87.66 mm. • Color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.47 kg.	
CM-CLEAR-64-11	Clear bubble for CM-640x mini-dome cameras: • Dimensions: 161 x 161 x 100 mm. • Outer ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.65 kg.	
CM-SMOKE-64-11	Smoked bubble for CM-640x mini-dome cameras: • Dimensions: 161 x 161 x 100 mm. • Outer ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.65 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.13 FLIR QUASAR™ Premium Mini-Dome AI (CM-640x-xx-AI)



Part number / item code	Description	Images
CX-ARMX-G3	Wall mount (1.5" PF inner thread): • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 249 (L) x 140 (W) x 227 (H) mm. • Color: White. • Shipping box size: 29 x 16 x 21 cm. • Shipping box weight: 1.27 kg.	
CX-ELBX-G3	Wall mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 316 (L) x 185 (W) x 228(H) mm. • Color: White. • Shipping box size: 29.5 x 21.5 x 22 cm. • Shipping box weight: 3.1 kg.	
CX-GSNK-G3	Gooseneck mount (1.5" PF inner thread) with IP66 electrical box enclosure: • Attaches directly to a wall. • Can be used with CX-CRNR-G3 corner mount and CX-POLE-G3 pole mount kits. • Can be used with FMS00003238. • Dimensions: 515 x 256 x 1043 mm. • Color White. • Shipping box size: 89 x 54 x 15.5 cm. • Shipping box weight: 13.55 kg.	
FMS00003238	PF-NPT adapter.	


CX-DRP-G32-B	Ceiling mount kit, including base and 20 cm drop-down pipe (1.5" PF inner thread): • Can be used with CX-PIPE-G325 50 cm extension pipe. • Dimensions: 165 x 257.5 mm. • Weight: 0.94 kg. • Color: White. • Shipping box size: 21 x 10 x 21 cm. • Shipping box weight: 1.02 kg.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	
CM-SECA-W4	Side conduit adapter kit, with cable housing attached: • Replaces mounting bracket included in the camera kit. • Attaches to standard electrical box or directly to mounting surface. • Dimensions: 191 x 157 x 52 mm. • Color: Grey. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 2.83 kg.	
CM-RCSD-G4	Recessed mount kit for CM-640x mini-dome cameras, including ceiling sticker template and trim ring: • Supports conduit connections. • Dimensions: 212 x 212 x 76 mm. • Trim ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 1.11 kg.	 Mounted with camera

CM-SNSHLD-G4	Sunshield for CM-640x mini-dome cameras: • Dimensions: 175.68 x 200.51 x 87.66 mm. • Color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.47 kg.	
CM-CLEAR-64-11	Clear bubble for CM-640x mini-dome cameras: • Dimensions: 161 x 161 x 100 mm. • Outer ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.65 kg.	
CM-SMOKE-64-11	Smoked bubble for CM-640x mini-dome cameras: • Dimensions: 161 x 161 x 100 mm. • Outer ring color: FLIR White. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 0.65 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.14 FLIR QUASAR™ Premium Bullet AI (CB-650x-x1-AI)



Part number / item code	Description	Images
CM-SECA-W4	Side conduit adapter kit, with cable housing attached.: • Replaces mounting bracket included in the camera kit. • Attaches to standard electrical box or directly to mounting surface. • Dimensions: 191 x 157 x 52 mm. • Shipping box size: 234 x 234 x 128 mm. • Shipping box weight: 2.83 kg.	
CM-4S-32	4S electrical box mount adapter plate: • For outdoor applications. • Can be used with DH-Series pendant mount accessories. • Dimensions: 142 (D) x 5 (H) mm. • Color: FLIR White.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	

CX-POLE-G32	Pole mount kit, including straps, for use with CM-CAPX-W32 wall mount with pendant cap kit: • Dimensions: 240 x 180 x 60 mm. • Pole diameter range: 130~152 mm. • Color: Cool Gray 2C.	
CB-BKBX-65	Back Box with 3/4" (20 mm) NPT conduit holes: • Included in the box with the camera. • Dual-hole, back and side.	
CB-BKBX-65S	Alternative Back Box: • Two 17 mm holes located at the rear.	 Back Box Mounting Plate
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.15 FLIR QUASAR™ Premium Fixed Box AI (CF-6408)



Part number / item code	Description	Images
CF-L408-11-0	1/1.8" 4.0-10 mm F0.9 IR Vari-focal Stepping Motor Iris Lens with P-Iris.	
CF-L408-11-1	1/1.8" 3.9-10 mm F1.5 IR Vari-focal Stepping Motor Iris Lens with P-Iris.	
CF-L408-21-1	1/1.8" 9.0-50 mm F1.5 IR Vari-focal Stepping Motor Iris Lens with P-Iris.	
CF-ENCL-64-0	Outdoor Mounting Kit, including: • Enclosure with fan, heater, and sunshield. • CF-ENCL-64-lx models include IR LED illumination. • Wall mount arm. • Pole mount adapter. • Pole mount rings (pole diameter range ø 2.5–8").	 <i>CF-ENCL-64-0 enclosure with sunshield</i>
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

4.16 FLIR QUASAR™ 4K Fixed Box (CF-6308)



Part number / item code	Description and notes	Images
CF-L308-11-I	Ultra HD i-CS Lens (3.9-10 mm). • Shipping box size: 490 x 360 x 330 mm.	
CF-L308-21-I	Ultra HD i-CS Lens (9-50 mm) • Shipping box size: 490 x 360 x 330 mm.	
CF-L304-21-P	Quad HD (1440p) lens, 12-50 mm, F1.5, 1/1.8", P-Iris, IR corrected, CS mount: • Shipping box size: 660 x 380 x 390 mm.	
CF-ENCL-63E-I CF-ENCL-63E-O	Outdoor high-temperature, vandal-proof enclosure and wall mount bracket: • Quick specs: CF-ENCL-63E-I model equipped with heater & IR LEDs. • Power (CF-ENCL-63E-I): 24 VAC @18-23W. • Compliance: IK10 / IP66. • Enclosure dimensions: 174 (W) x145 (H) x422 (L) mm. • Color: FLIR White. • Shipping box size: 73 x27 x27 cm. • Shipping box weight: ○ CF-ENCL-63E-I: 5.3 kg. ○ CF-ENCL-63E-O: 5.1 kg. • Temperature range: ○ CF-ENCL-63E-I with IR LEDs on: -20 to +50 °C / -4 to +122 °F. ○ CF-ENCL-63E-I with IR LEDs off/ CF-ENCL-63E-O : -20 to +50 °C / -4 to +140 °F.	

CX-POLE-G63	Pole mount adapter for CF-ENCL-63E-x; includes straps: • Dimensions: 238 x 260 x 60 mm. • Pole diameter range: $\varnothing$ 130-152 mm. • Color: Cool gray 1C. • Shipping box size: 64 x 42 x 33 cm. • Shipping box weight: 13.8 kg.	 <i>With enclosure</i>
CF-E-63	Outdoor environmental housing: • Specs when equipped with Heater & Fan: • Power: 24 VAC @20 W. • Housing: Top: ABS & PC, Bottom: Aluminum, Sunshield: Aluminum. • Compliance: IK10 / IP68. • Suitable camera size: 108 (W) x 75 (H) x 300 (L) mm. • Dimensions including sunshield: 161 (W) x 141 (H) x 360 (L) mm. • Temperature range: -20 to +50 °C (-4 to +122 °F). • Color: White. • Shipping box size: 58 x 38 x 48 cm. • Shipping box weight: 17.3 kg.	 <i>Without sunshield</i>
CF-POLE-63	Pole mount adapter for CF-ENCL-63; includes straps: • Dimensions: 152 (L) x 161 (W) x 73 (D) mm. • Pole diameter range: $\varnothing$ 2.5–8.5". • Color: White. • Shipping box size: 37.5 x 26.5 x 37.5 cm. • Shipping box weight: 1.29 kg.	
4210755 FC-PWR-00	Inline 30 W IEEE 802.3at PoE+ injector: • Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at. • 100-240 VAC input.	

5. Radar

5.1 FLIR ELARA™ R-SERIES RADAR



Part number / item code	Description	Images
421-0083-00	180° dual-unit wall mount kit.	
CX-CRNR-G3	90-degree exterior angle corner mount kit: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Dimensions: 404 (L) x 239 (D) x 200 (H) mm. • Color: White. • Shipping box size: 38 x 21 x 12.5 cm. • Shipping box weight: 4.67 kg.	
CX-POLE-G3	Pole mount kit, including straps: • Can be used with CX-ELBX-G3, and CX-ARMX-G3 wall mount kit; and with CX-GSNK-G3 gooseneck mount. • Pole diameter range: 150-230 mm (2.5-8.5"). • Dimensions: 240 (L) x 161(w) x 72.5 (D) mm. • Color: White. • Shipping box size: 25 x 18 x 8 cm. • Shipping box weight: 2.1 kg.	

4210755

FC-PWR-00

Inline 30 W IEEE 802.3at PoE+ injector:

- Supports FLIR Security Edge devices that can be powered by PoE+ IEEE 802.3at.
- 100-240 VAC input.



6. Disclaimer

By providing this document, Teledyne FLIR LLC is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

© Teledyne FLIR LLC 2026. All rights reserved.

Teledyne FLIR LLC
Antennvägen 6
PO Box 7376, SE-187
15 Täby
Stockholm County, 187 66
Sweden

Support:
<https://support.flir.com/>