

PRO SERIES ROCK SPEAKERS

With IMG woofers and a Tractrix horn-loaded Aluminum Dome Tweeter, the Pro Series rock speaker uses the same high performance acoustic design philosophies of our legendary indoor products, bringing the world's most dynamic, powerful, detailed sound to your outdoor living space.

From small residential systems to massive commercial installs, the Klipsch Pro Series rock speakers are designed to make any installation job quick and easy. For distributed line application, the Pro Series rock speakers feature a 70V/100V multi-tap transformer with 8 ohm bypass, allowing for exceptional balance at any listening location - all selectable from an easily accessible, tool-free rotary switch on the back of the speaker.



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 70V/100V multi-tap transformer with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

PRO-500T-RK 5" 2-WAY ROCK SPEAKER

FREQUENCY RANGE	130Hz - 30kHz +/- 3dB 113Hz - 32kHz +/- 6dB 93Hz - 36kHz +/- 10dB
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
LOW FREQUENCY DRIVER	5" (12.7cm) IMG Woofer
SENSITIVITY	88 dB
COVERAGE ANGLE	105°
POWER HANDLING	60W Peak
70V / 100V TAP SETTINGS	70V: 3.75W, 7.5W, 15W, 30W 100V: 7.5W, 15W, 30W 8 Ohm Bypass
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite or Sandstone
PRODUCT DIMENSIONS	9.21" x 9.72" x 10.43" (234mm x 247mm x 265mm)
PRODUCT WEIGHT	8 lbs (3.62 kg)

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 11.2 lbs

PART NUMBER

1063228 (Granite)

1063227 (Sandstone)

NOTES:



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 70V/100V multi-tap transformer with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

PRO-650T-RK 6.5" 2-WAY ROCK SPEAKER

FREQUENCY RANGE	100Hz - 24kHz +/- 3dB 92Hz - 30kHz +/- 6dB 77Hz - 35kHz +/- 10dB
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum Dome Tweeter mated to an all new 105° custom Tractrix® horn
LOW FREQUENCY DRIVER	6.5" (16.51cm) IMG Woofer
SENSITIVITY	90 dB
COVERAGE ANGLE	105°
POWER HANDLING	100W Peak
70V / 100V TAP SETTINGS	70V: 6.25W, 12.5W, 25W, 50W 100V: 12.5W, 25W, 50W 8 Ohm Bypass
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite or Sandstone
PRODUCT DIMENSIONS	10.91" x 9.65" x 13.43" (277mm x 245mm x 341mm)
PRODUCT WEIGHT	11 lbs (4.98 kg)

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 14.7 lbs

PART NUMBER

1063230 (Granite)

1063229 (Sandstone)

NOTES:



- All-new custom Tractrix® Horn provides ultra-wide 105° horizontal dispersion
- 70V/100V capability with 8-ohm bypass
- UV-resistant, mechanically reinforced fiberglass cabinet

PRO-10SW-RK 10" ROCK SUBWOOFER

FREQUENCY RANGE	47Hz - 103Hz +/- 3dB
	40Hz - 110Hz +/- 6dB
	33Hz - 123Hz +/- 10dB
SYSTEM TYPE	Sealed box
WOOFER	10" (25.4cm) IMG Dual Voice Coil
SENSITIVITY	90 dB
POWER HANDLING	200W
IMPEDANCE	70V @ 250W (Transformerless)
	8 Ohm Stereo
	4 Ohm Mono
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite or Sandstone
PRODUCT DIMENSIONS	13.39" x 18.43" x 20.67" (340mm x 468mm x 525mm)
PRODUCT WEIGHT	30 lbs (13.6 kg)

SHIPPING QUANTITY: Single

SHIPPING WEIGHT: 35.4 lbs

PART NUMBER

1063232 (Granite)

1063231 (Sandstone)

NOTES:

