



LTE-KCN

Advanced Modular Communicator

For VISTA and Competitive Control Panels

Resideo is committed to providing the best alarm communication solutions for the security industry. Our LTE® Communicators utilize the latest LTE technology to communicate with AlarmNet®.

Resideo Communicators easily connect to customers' security system control panels and sends alarms and messages to AlarmNet for transfer to the central monitoring station.

The LTE-KCN also support these optional plug-in modules:

- Wi-Fi®/Z-Wave® Module for Wi-Fi connection to the Internet and/or for control of home automation devices (model PROWIFIZW)
- Dialer Capture Module for use with control panels that send Contact ID signals via Dialer (model PRODCM)
- Wi-Fi Module for Wi-Fi connection to Internet



Features & Benefits

- Quick connection to Resideo control panels and non-Resideo compatible control panels (see panel compatibility)
- Supports both ECP and Bus connections to compatible control panels
- Powered by the control panel's 12VDC auxiliary output
- Supports dynamic or static IP addressing, and installs behind firewalls without compromising network security (Ethernet only, WIFI does not support STATIC addressing)
- Supports connection to the Internet via Ethernet cable or Wi-Fi (Wi-Fi requires installation of PROWIFIZW or PROWIFI module) – only one method can be used, Ethernet or Wi-Fi, not both
- Reports alarms and status messages via the Internet (LTE communicators provide cell radio backup reporting)
- Allows uploading and downloading of VISTA control panel data
- Supports Remote Services feature, which allows the end user to access their security system from their computer via a website. Availability of this service is controlled by the dealer via the web-based programming tool on the AlarmNet 360 website
- Multi-function Test switch used to generate test messages, register the communicator with AlarmNet, enter Pairing mode (used during Wi-Fi module installation), reboot the communicator, and to reset the communicator to factory default settings

LTE-KCN Advanced Modular Communicator Specifications

PANEL COMPATIBILITY

DSC® PowerSeries™ Compatibility:
PC1616, PC1832, PC1864

Interlogix® NetworX Series Compatibility:
NX-8E, NX-4V2, NX-6V2, NX-8V2

Honeywell Home:
VISTA-15P V9.12+,
VISTA-20P V9.12+,
VISTA-21iP V3.13+

Resideo:
VISTA-128BPT V10.0+,
VISTA-250BPT V10.3+

DIMENSIONS

18.6 cm x 22.8 cm x 4.4 cm
(7.3" x 9.0" x 1.7")

WEIGHT

510g

ELECTRICAL

Input power: 12VDC supplied by the control panel

CURRENT DRAIN

Stand-Alone Unit:
235mA average active

With Wi-Fi®/ZW Module:
290mA average active

With Dialer Capture Module:
245mA average active

Wi-Fi/ZW and Dialer Capture Modules:
325mA average active

BACKUP BATTERY

None

RF

Antenna:
Penta-Band diversity antennas
BLE internal antenna

ENVIRONMENTAL

Operating temperature:
0°C to +49°C (32°F to 120°F)

Storage temperature:
-40°C to +70°C (-40°F to 158°F)

Humidity: to 95% relative humidity,
non-condensing;
for ULC installations 0% to 93%;

Altitude: Up to 3,048m (10,000 ft.)
operating; to 12,192m (40,000 ft.)
storage

DEVICES

**78 Z-Wave® Plus Devices available
when PROWIFIZWAVE module is added:**

60 Lights, Water Valves, Shades

6 Thermostats

6 Locks

6 Garage Door Controls

APPROVALS

**These devices have been tested by ETL
to meet the following standards:**

CAN/ULC-S304:2016 ed.3+R1 Control
Units, Accessories and Receiving
Equipment for Intrusion Alarm Systems

CAN/ULC-S545:2002 Ed.2 Residential
Fire Warning System Control Units

ETHERNET®

Network Standard: IEEE 802.3u
compliant

Data Rate: 10Base-T (10Mbps) /
100Base-T (100Mbps) with auto detect

Ethernet Cable: Cat. 5 (min), MDI /
MDI-X auto crossover

WIRE LENGTHS

**ECP and BUS connection maximum
wire lengths:**

MINIMUM WIRE GAUGE	DISTANCE FROM CONTROL PANEL
#22	23m (75 ft)
#20	37m (120 ft)
#18	52m (170 ft)
#16	82m (270 ft)

EXTERNAL ANTENNA COMPATIBILITY

PROLTE-ANT

CELL-ANT3DB

ORDERING

LTE-KCN	LTE® Cat-1 Cellular and Internet Communicator, Bell®
PROWIFIZW	Wi-Fi/Z-Wave Module for Wi-Fi connection to the internet and/or for control of home automation devices
PRODCM	Dialer Capture Module for use with control panels that send Contact ID signals via Dialer
PROWIFI	Wi-Fi Module for Wi-Fi connection to the internet

resideo

For more information
resideo.com

Resideo Technologies, Inc.
90 Burnhamthorpe Road West
14th Floor
Mississauga, ON L5B 3C3
Office: 1-800-645-7492

L/LTEKCN/D | AF | 02/23
© 2023 Resideo Technologies, Inc.
All rights reserved.
The Honeywell Home trademark is used under
license from Honeywell International Inc.
These products are manufactured by Resideo
Technologies, Inc. and its affiliates.