

# Cora™ CN-73 Well Light



|           |
|-----------|
| PROJECT   |
| CATALOG # |
| TYPE      |
| NOTES     |

The low-profile CN-73 offers smart glare control with an exclusive reversible housing and strong debris protection from an integrated polycarbonate lens. Featuring superior material quality, an intuitive installation process, and unmatched flexibility, it’s the go-to solution for projects demanding precision, discretion, and resilience.

## Quick Facts

- Low-profile linear grate design enables seamless installations
- Reversible housing offers an angled side for glare control and a flat side for flush installs
- Durable select brass faceplate stands up to harsh environments
- Tough polycarbonate lens keeps debris out
- Aimable PAR-36 LED lamp allows precise beam targeting
- Ideal for landscapes requiring a rugged, adjustable well light

# Cora™ CN-73 Well Light SPECIFICATIONS

|                                    | E9WFL      | E9SFL      | E12WFL     | E12SFL     |
|------------------------------------|------------|------------|------------|------------|
| Total Lumens (lm)                  | 400        | 430        | 570        | 570        |
| Power Consumption (VA)             | 8.5        | 8.5        | 11.3       | 11.3       |
| Efficacy (lm/W)                    | 69         | 73         | 64         | 64         |
| Correlated Color Temperature (CCT) | 2700K      | 3000K      | 2700K      | 3000K      |
| Beam Angle                         | 35°        | 35°        | 35°        | 35°        |
| Maximum Candela (cd)               | 450        | 770        | 520        | 1,015      |
| Color Rendering Index (CRI)        | 85+        | 85+        | 85+        | 85+        |
| Input Voltage (V)                  | 10-15      | 10-15      | 10-15      | 10-15      |
| Minimum Rated Life (L70)           | 50,000 Hrs | 50,000 Hrs | 50,000 Hrs | 50,000 Hrs |

# Cora™ CN-73 Well Light SPECIFICATIONS

## About FX Luminaire

As a leading manufacturer of landscape and architectural lighting, FX Luminaire provides innovative products, resources, and support to help customers bring their visions to life. The company offers a range of specification-driven solutions, including fixtures, controls, and accessories, to enhance residential and commercial landscapes.

## Materials

Select brass faceplate with stainless steel hardware.

## Dimming

Primary: Consult transformer specifications. Secondary: Luxor® control (with Luxor CUBE) or a trailing-edge (reverse phase-cut) dimmer.

## Adjustability

The light source offers 2.5" (64 mm) of internal height adjustability and a 20° tilt capability.

## Finish

Antique Bronze finish sealed with a clear TGIC powder-coated layer or black polyester TGIC powder-coated layer, providing superior outdoor weathering in all conditions. Tested to ASTM standards.

## Wiring

16 AWG (1.5 mm); SPT-2W; 220°F (105°C); 300 V; 26' (8 m) length

## Sockets

Accepts standard sealed-beam PAR-36 LED Lamps equipped with bottom-positioned terminal screw connectors for direct-wire installation.

## Housing

Designed to accept standard PAR-36 LED Lamps conforming to ANSI C78.21 specifications, with a maximum diameter of 4.5" (115 mm) and a maximum overall height of 2.8" (70 mm).

## Weight

3.4 lb (1.5 kg)

## Lens

Impact and UV Resistant Polycarbonate Lens.

## Ambient Operating Temperature

0°F to 140°F (-18°C to 60°C)

## Input Voltage

10-15 VAC/VDC, 50/60 Hz. Remote transformer required (specify separately).

## Power Consumption

Specified power consumption indicates the full apparent power.

## Installation Requirements

Designed for installation in the upward direction only

## Lens Transparency

Clear

## Manufacturing

9001:2015 ISO certified facility

## Warranty

Fixture: Limited 10-year warranty  
Preinstalled Lamp: Limited 3-year warranty

## Listings



# Cora™ CN-73 Well Light ORDERING INFORMATION

| Fixture | Power                                      | Color Temp               | Beam Angle               | Faceplate                 | Finish                      |
|---------|--------------------------------------------|--------------------------|--------------------------|---------------------------|-----------------------------|
| CN-73   | <b>E9</b><br>8.5 VA, PAR-36 Eco LED Lamp   | <b>W</b><br>Warm (2700K) | <b>FL</b><br>Flood (35°) | <b>LG</b><br>Linear Grate | <b>FB</b><br>Black          |
|         | <b>E12</b><br>11.3 VA, PAR-36 Eco LED Lamp | <b>S</b><br>Soft (3000K) |                          |                           | <b>AB</b><br>Antique Bronze |
|         | <b>NL</b><br>Lamp not included             |                          |                          |                           |                             |

-

-

-

-

-

EXAMPLE FIXTURE CONFIGURATION: CN-73-XX-XXXX-XX



POWER OPTIONS: Specify Separately

| Power                                           | Catalog No. |                                                                                   | Power                               | Catalog No. |                                                                                     |
|-------------------------------------------------|-------------|-----------------------------------------------------------------------------------|-------------------------------------|-------------|-------------------------------------------------------------------------------------|
| Low-Voltage Dimmer                              | DIM-LV      |  | Luxor Low-Voltage CUBE              | LCM-LV      |  |
| Mini Plug-In Transformer, 30 W                  | MT-30W      |  | Plug-In Transformer, 6 W            | MT-6W       |  |
| Step-Down Transformer, Dimmable (120 V to 12 V) | ST-120-DIM  |  | Step-Down Transformer (120V to 12V) | ST-HV       |  |
| Step-Down Transformer, UV (120/277 V to 12 V)   | ST-UV       |  |                                     | SURGE-MOD   |  |

SPLICING OPTIONS: Specify Separately

| Splicing                                     | Catalog No. |                                                                                   |
|----------------------------------------------|-------------|-----------------------------------------------------------------------------------|
| Brass Lug Wire Connectors, 2-pack            | WCHSBS2     |  |
| Heat Shrink Wire Connectors, 20-pack, Medium | WCHSMD20    |  |

| Splicing                                     | Catalog No. |                                                                                     |
|----------------------------------------------|-------------|-------------------------------------------------------------------------------------|
| Brass Lug Wire Connectors, 50-item Bulk Pack | WCHSBS50    |  |
| Heat Shrink Wire Connectors, 20-pack, Small  | WCHSSM20    |  |