



BRR-P1H1SH1

BLAZE Server

Key Features

The BRR-P1H1SH1 BLAZE Recording Server sets the bar for power, reliability, and ease of use. The BRR-P1H1SH1 is pre-installed with BLAZE and five full-featured 30-day onboarding licenses. This high-reliability rackmount server is ready to scale as part of a multi-site BLAZE federated organization and can be combined with BLAZE Recording Appliances.

Fast Deployment, Cloud-driven Scalability

- Intel Xeon 6333P
- Windows Server 2022 protected by a RAID 1 OS drive
- 128 channel and 470 Mbps recording bandwidth capacity
- Up to 80 TB storage with RAID 0/1/5/6/10 redundancy
- Dual redundant power supplies
- BLAZE preinstalled with five temporary 30-day onboarding licenses
- Supported by BLAZE VMS Desktop Client, Mobile, and Web Client
- Supports Federation via Hanwha Vision Cloud
- Supports Similarity Search and AI metadata

** Licenses for BLAZE and optional Software Update Plans available separately*

BRR-P1H1SH1

BLAZE Server

Specifications

System		
Video Management Software		BLAZE VMS
Licenses		No License
Available Channels		Up to 128 channels
Recording Rate		Up to 470Mbps
OS Drive Bays		SSD 2 x 480GB RAID 1
Data Drive Bays		SATA 4ea
Data Storage		Up to 80TB
RAID Support		RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
Network Interface		2 x RJ-45 (1Gbps), Optional: 2 x RJ-45(1Gbps) + 2 x RJ-45(10Gbps)
Processor		Intel Xeon 6333P
Memory		16GB DDR5
Operating System		Windows Server 2022
IPMI		Supported
Decoding	Video Outputs	1 x VGA, NVIDIA Quadro T400 3 x mDP, 1x mDP to HDMI adapter
USB Ports		Front: 2 x USB 3.2 Rear: 2 x USB 3.2
Other Ports		Serial
Keyboard & Mouse		Keyboard, Mouse
Sliding Rail Kit		Included, with Cable Management Arm
Security		
Security Certificate		UL/cUL equivalent (MET/Eurofins), CE, FCC (Class A), BSMI
Mechanical		
Form Factor		1U rack
Color / Material		Black / Metal
Dimensions (WxHxD)		17.3"(440mm) x 1.7"(44mm) x 19.6"(498mm)
Weight		50 lbs (23 kg)
Electrical		
Power Input		100 ~ 240 VAC $\pm$ 10%, 50/60 Hz
Power Supply		2 x 450W 80 Plus Platinum
Power Consumption		1725 Max BTU/hr

Environmental

Operating Temperature	50°F to 95°F(10°C to 35°C)
Storage Temperature	-40°F to 158°F(-40°C to 70°C)
Operating Humidity	10% to 80% RH (non-condensing)