



BRT-X641W1

BLAZE Server/Workstation

Key Features

The BRT-X641W combines BLAZE recording server and client workstation functionality into a single, versatile, Windows-based machine. The unit is pre-installed with BLAZE and five full-featured 30-day onboarding licenses. This tower form factor device is perfect for up to 64 channels. It is ready to scale as part of a multi-site BLAZE federated organization and can be combined with BLAZE Recording Appliances and Servers.

Fast Deployment, Cloud-driven Scalability

- Tower form factor server/workstation
- Up to 64 channels
- Up to 36 TB storage
- 470 Mbps recording bandwidth capacity
- 14th Intel Ultra 5 running Windows 11 IoT Enterprise LTSC 2024
- 2x DP with 1 DP-HDMI adaptor monitor outputs
- Keyboard, and mouse included
- BLAZE preinstalled with five temporary 30-day onboarding licenses
- Supported by BLAZE VMS Desktop Client, Mobile, and Web Client
- Supports Federation via Hanwha Vision Cloud
- Supports Similarity Search and AI metadata

** Licenses for BLAZE and optional Software Update Plans available separately*

BRT-X641W1

BLAZE Server/Workstation



Specifications

System		
Video Management Software		BLAZE VMS
Licenses		No License
Available Channels		Up to 64 channels
Recording Rate		Up to 470Mbps
OS Drive Bays		SSD 512GB
Data Drive Bays		SATA 3ea
Data Storage		Up to 36TB
Network Interface		1 x RJ-45 (1Gbps), 1 x RJ-45 (5Gbps)
Processor		Intel Core Ultra 5
Memory		16GB DDR5
Operating System		Windows 11 IoT Enterprise LTSC 2024
Decoding	Video Outputs	2 x DP, 1 x DP to HDMI adapter
USB Ports		Front: 2 x USB 3.2 Gen1, 1x USB 3.2 Gen2 Type C, 1 x USB 3.2 Gen 2x2 Type C Rear: 2 x USB 2.0 2 x USB 3.2 Gen 2, 1 x USB 3.2 Gen 2x2 Type C, 1 x Type C Thunderbolt
Audio	Output	Front: 1 x 3.5mm Universal Audio
Keyboard & Mouse		Keyboard, Mouse
Security		
Security Certificate		UL, cUL, CB, FCC, 80 Plus Platinum
Mechanical		
Form Factor		Tower
Color / Material		Black / Metal
Dimensions (WxHxD)		7.40"(187.70mm) x 15.24"(387mm) x 17.24"(438mm)
Weight		44.97 lbs (20.40 kg)
Electrical		
Power Input		100 ~ 240 VAC ±10%, 50/60 Hz
Power Supply		1500W 80 Plus Platinum

Environmental

Operating Temperature	41°F to 113°F(5°C to 45°C)
Storage Temperature	-40°F to 158°F(-40°C to 70°C)
Operating Humidity	20% to 85% RH (non-condensing)