

Specifications

Eaton B004-DP2UA2-K

2-Port DisplayPort KVM Switch 4K 60 Hz with Audio, Cables and USB Peripheral Sharing

General specifications

PRODUCT NAME	Eaton Tripp Lite series KVM switch
CATALOG NUMBER	B004-DP2UA2-K
UPC	037332193179
PRODUCT LENGTH/DEPTH	9.4 in
PRODUCT HEIGHT	2.4 in
PRODUCT WIDTH	6.7 in
PRODUCT WEIGHT	1.3 lb
COMPLIANCES	RoHS
GLOBAL CATALOG	B004-DP2UA2-K
PRODUCT TYPE	KVM switch

Product specifications

LED INDICATORS	KVM FOCUS (ILLUMINATES SOLID); AUTO-SCAN (FLASHES)
MATERIAL OF CONSTRUCTION	Metal
OPERATING TEMPERATURE RANGE	32° to 122°F (0° to 50°C)
RELATIVE HUMIDITY	0-80% non-condensing
STORAGE TEMPERATURE	-4° to 140°F (-20° to 60°C)
COMPUTER/SERVER PORTS	DP, USB, 3.5mm Audio Jack (Audio)
NUMBER OF MONITORS	1
OPERATING TEMPERATURE	• 32° to 122°F (0° to 50°C) • 32° to 122°F (0° to 50°C)
NUMBER OF USERS	1
CPU	2
DAISY-CHAIN PORT	No
FIRMWARE UPGRADE PORT	No
KEY TYPE	Yes
MAX NUMBER OF PORTS	2
COLOR	Black
AUTOSCAN	Yes
CABLE JACKET COLOR	Black
PACKAGE CONTENTS	(2) DisplayPort monitor cables Owner's manual B004-DP2UA2-K 2-Port DisplayPort KVM Switch 4K 60 Hz (2) USB A/B device cables Remote port selector (2) 3.5 mm stereo audio cables
SYSTEM REQUIREMENTS	3.5 mm audio jack (if using audio function) Speakers with 3.5 mm male connector (if using audio function) DisplayPort audio/video port (connecting non-DP computers is not recommended) DisplayPort monitor capable of supporting highest resolution of any

Resources

MANUALS AND USER GUIDES	Owner's Manual for B004-DP2UA2-K (Multi-language)
TECHNICAL DATA SHEETS	HOW TO USE THE B005-DPUAX SERIES MOUSE TRAVERSAL FUNCTION
	HOW TO TROUBLESHOOT B07X-SERIES KVM SWITCHES FOR LDAP
	HOW TO USE THE B005-HUAX SERIES MOUSE TRAVERSAL FUNCTION

	computer in installation USB port USB keyboard/mouse
PRODUCT FEATURES	Bus Powered MST Support EDID Compatible
USB SPECIFICATION	USB 2.0 (up to 480 Mbps)
SIDEA CONNECTOR1	DISPLAYPORT (FEMALE)
SIDEB CONNECTOR1	3.5MM (FEMALE) DISPLAYPORT (FEMALE)
SIDEA CONNECTOR2	3.5MM (FEMALE)
SIDEB CONNECTOR2	3.5MM (FEMALE)
SIDEA CONNECTOR3	USB B (FEMALE)
SIDEB CONNECTOR3	DISPLAYPORT (FEMALE) USB A (FEMALE)
DISPLAYPORT SPECIFICATION	1.2
PORT CONTROL	Hotkeys, OSD, Remote Toolbar Hotkeys, OSD, remote toolbar
PC/SERVER CONNECTIONS	USB DisplayPort
TECHNOLOGY	DisplayPort Stereo Audio USB 2.0 (High Speed)
AUTOSCAN DURATION	CAN BE SET TO 3, 5, 10 OR 20 SECONDS, WITH 5 SECONDS BEING THE DEFAULT
MAX SUPPORTED VIDEO RESOLUTION	3840 x 2160 (4K x 2K) @60 Hz

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

