

Specifications

Eaton N600P-576U-24

High-Density Fiber Patch Panel, 4U w 24x Splice Cassettes, 576x LC/UPC SM 0.9mm, 1.5M Pig-tail

General specifications

PRODUCT NAME	Eaton Tripp Lite series fiber patch panel and cassette and enclosure
CATALOG NUMBER	N600P-576U-24
PRODUCT LENGTH/DEPTH	18.5 in
PRODUCT HEIGHT	6.93 in
PRODUCT WIDTH	19 in
PRODUCT WEIGHT	30.2 lb
COMPLIANCES	REACH RoHS
GLOBAL CATALOG	N600P-576U-24
PRODUCT TYPE	Fiber patch panel and cassette and enclosure

Product specifications

TYPE	Fiber Patch Panel
PACKAGE CONTENTS	(576) Single-splicing protective tubes (10) Nylon cable ties Mounting hardware Spiral wrapping band N600P-576U-24 4U Panel Fiber Splice Enclosure Velcro tie Owner's manual
CONNECTOR COLOR	Green
PRODUCT FEATURES	Built-in Cable Management Mounting Accessory Included Numbered Ports Labeled Ports Rackmountable
NETWORK SPEED	40 Gbps 100 Gbps 1 Gbps (Gigabit) 10 Gbps 25 Gbps 400 Gbps 800 Gbps
SIDE A CONNECTOR1	LC
TECHNOLOGY	Singlemode
OPERATING HUMIDITY	5% to 85% RH, non-condensing
OPERATING TEMPERATURE RANGE	14° to 140° F (-10° to 60° C)
STORAGE HUMIDITY RANGE	5% to 85% RH, non-condensing
STORAGE TEMPERATURE	14° to 140° F (-10° to 60° C)
INSERTION LOSS	≤0.30dB
NUMBER OF FIBERS	576
PANEL DIMENSIONS	19.10 x 8.86 x 18.51
PRIMARY FORM FACTOR	Rackmount
MATERIAL OF CONSTRUCTION	Metal
CASSETTE CAPACITY	24
NUMBER OF CASSETTE SPLICING TRAYS	24
SPLICING TRAY DIMENSIONS (HWD/MM)	12.5 x 196.2 x 295
CASSETTE SPLICING TRAY CAPACITY	24 fibers
CASSETTE PATCH CORD	LC/UPC Singlemode, 1.5 M

Resources

	Pigtail, 0.9 mm
MINIMUM REQUIRED RACK DEPTH	19 in
RACK UNITS	4
MOUNTING DETAILS	RACK MOUNT
WAVELENGTH	1550 nm
CONNECTOR	LC
ATTENUATION 1550NM	≤0.30dB/KM
ENDFACE POLISH	UPC
FITTINGS INCLUDED	Mounting Accessory Included
OPTICAL MODE	SM OS2
MODE	Singlemode
OPTICAL PORT	LC

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

