

Specifications

Eaton PDUMV20-ISO

Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, NEMA L5-20P/5-20P input, 15 ft cord, 1.92kW, 16A, 120V, 28 Outlets (28) 5-20R - Surge Protected

General specifications

PRODUCT NAME	Eaton Tripp Lite series local metered rack PDU
CATALOG NUMBER	PDUMV20-ISO
UPC	037332255884
PRODUCT LENGTH/DEPTH	3.14 in
PRODUCT HEIGHT	60.43 in
PRODUCT WIDTH	1.5 in
PRODUCT WEIGHT	6.88 lb
COMPLIANCES	RoHS TAA Compliant
CERTIFICATIONS	UL 1449 UL Listed NOM RETIE UL 62368-1 CSA Std. C22.2
GLOBAL CATALOG	PDUMV20-ISO
PRODUCT TYPE	Rack PDU

Product specifications

FORM FACTOR	0U (Vertical)
ACCESSORIES	BUTTON MOUNTS
PACKAGE CONTENTS	• PDUMV20-ISO 1.92kW 120V Single-Phase Local Metered PDU • L5-20P to 5-20P plug adapter • Mounting hardware • Owner's manual

OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
------------------------------	---------------------------

MOUNTING DIRECTION	Vertical
---------------------------	----------

MATERIAL	Aluminum
-----------------	----------

CORD LENGTH	15 ft
--------------------	-------

AMPERAGE RATING	16A
------------------------	-----

ELECTRIC CURRENT - MAX	16
-------------------------------	----

INPUT VOLTAGE	120V
----------------------	------

PHASE	Single-phase
--------------	--------------

FREQUENCY RATING	50/60 Hz
-------------------------	----------

NUMBER OF OUTPUTS 5-20R	28
--------------------------------	----

FEATURES	Flex Center
-----------------	-------------

FRONT PANEL LCD DISPLAY	Digital meter reports PDU output current in amps
--------------------------------	--

OUTPUT RECEPTACLES	5-15/20R
---------------------------	----------

AC SUPPRESSION JOULE RATING	3840
------------------------------------	------

AC SUPPRESSION RESPONSE TIME	NM = 0 ns. CM = <1 ns
-------------------------------------	-----------------------

EMI/RFI FILTERING	40-80 dB
--------------------------	----------

AC SUPPRESSION SURGE CURRENT RATING	60,000 amps
--	-------------

CLAMPING VOLTAGE	140
-------------------------	-----

LED INDICATORS	3 diagnostic LEDs continuously report status for LINE OK (green), suppressor or wiring FAULT (red) and PROTECTION PRESENT (green)
-----------------------	---

OVERLOAD PROTECTION	20A circuit breaker
----------------------------	---------------------

PROTECTION TYPE	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge
------------------------	--

Resources

	suppression
RECOMMENDED ELECTRICAL SERVICE	Single-phase 20A 120V service
RECEPTACLES	5-15/20R
RECEPTACLE COLOR	BLACK
IMMUNITY	Conforms to IEEE 587 / ANSI C62.41
MOUNTING DETAILS	Mounting Buttons
INPUT CORD LENGTH	15 ft
SWITCH CONFIGURATION	Lighted on/off switch with integrated transparent safety cover
TAA COMPLIANCE	Yes
PRODUCT FEATURES	TAA Compliant
AMPERAGE RATING DETAILS	Agency de-rated to 16A continuous
OPERATING ELEVATION	0-6562 ft. (0-2000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	120V
RELATIVE HUMIDITY	5-95% non-condensing
FORM FACTORS SUPPORTED	Vertical
OUTPUT CAPACITY DETAILS	1.92kW (120V) / 16A total capacity; 16A max per outlet
OUTPUT CAPACITY (KW)	1.92
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PDU PLUG TYPE	L5-20P
PDU TYPE	Local metered
PDU INPUT VOLTAGE	120
PDU FORM FACTOR	Vertical (0U)
TOTAL OUTLETS	28

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

