


Specifications



Eaton

EMAGECC4C4C4C4L

3-Phase Managed HDX Rack PDU G4,
240/415V, 24 C39 Outlets, 64A, 46kW,
Hardwired Input, 0U Vertical, TAA

General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMAGECC4C4C4C4L
UPC	037332296177
PRODUCT LENGTH/DEPTH	2.48 in
PRODUCT HEIGHT	69.45 in
PRODUCT WIDTH	4.09 in
PRODUCT WEIGHT	28.02 lb
COMPLIANCES	CE Marked FCC Class A TAA Compliant
CERTIFICATIONS	UL Listed cUL Listed
PRODUCT TYPE	Managed PDU

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Three-phase
AMPERAGE RATING	48A
INPUT CONNECTION	Hardwire
OUTLETS	24
CORD LENGTH	0
FREQUENCY RATING	50/60 Hz
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

