


Specifications



Eaton

EMAGKEC3C3C3C3L

3-Phase Managed HDX Rack PDU G4, 208V,
36 Outlets (24 C13 + 12 C39), 100A, 36kW,
Hardwired Input, 0U Vertical, TAA

General specifications

PRODUCT NAME	Eaton managed PDU
CATALOG NUMBER	EMAGKEC3C3C3C3L
UPC	037332296290
PRODUCT LENGTH/DEPTH	2.48 in
PRODUCT HEIGHT	69.45 in
PRODUCT WIDTH	4.09 in
PRODUCT WEIGHT	28.02 lb
COMPLIANCES	CE Marked FCC Class A TAA Compliant
CERTIFICATIONS	UL Listed cUL Listed
PRODUCT TYPE	Managed PDU

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	Yes
PHASE	Three-phase
AMPERAGE RATING	100A
INPUT CONNECTION	Hardwire
OUTLETS	36
CORD LENGTH	0
FREQUENCY RATING	50/60 Hz
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

