

# Specifications



## Eaton 5S700G

Eaton 5S UPS, 700 VA, 420 W, C14 input,  
Outputs: (6) C13

### General specifications

|                             |                                                                                |
|-----------------------------|--------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton 5S UPS                                                                   |
| <b>CATALOG NUMBER</b>       | 5S700G                                                                         |
| <b>UPC</b>                  | 743172043573                                                                   |
| <b>PRODUCT LENGTH/DEPTH</b> | 10.2 in                                                                        |
| <b>PRODUCT HEIGHT</b>       | 9.8 in                                                                         |
| <b>PRODUCT WIDTH</b>        | 3.4 in                                                                         |
| <b>PRODUCT WEIGHT</b>       | 13.1 lb                                                                        |
| <b>WARRANTY</b>             | 3 year factory warranty with online product registration                       |
| <b>COMPLIANCES</b>          | CE Marked<br>CCC Marked<br>FCC Part 15<br>C-Tick Compliant<br>CISPR 22 Class B |
| <b>CERTIFICATIONS</b>       | EN 62040-2:2006                                                                |
| <b>PRODUCT TYPE</b>         | UPS                                                                            |

## Battery

**RUNTIME GRAPH** [View runtime graph](#)

### BATTERY MANAGEMENT

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

## Electrical input

**INPUT CONNECTION** C14

**INPUT NOMINAL VOLTAGE** 230V

**INPUT VOLTAGE RANGE** 175-275 V

**INPUT FREQUENCY RANGE** 46-70 Hz (50 Hz system);  
57-70 Hz (60 Hz system)

## Environmental

**NOISE LEVEL** <25 dB at 1 meter

**TEMPERATURE RANGE** 0° to 35°C (32° to 95°F)

**RELATIVE HUMIDITY** 0-93% non-condensing

## Electrical output

**BATTERY TYPE** Sealed, lead-acid

**RECEPTACLE** (6) C13

**VA RATING** 700 VA

**WATTAGE** 350 W

**OUTPUT NOMINAL VOLTAGE** 220/230/240V

**TOPOLOGY** Line-interactive

## Communications

**COMMUNICATION** USB HID port as standard,  
6-ft USB cable included

**SOFTWARE COMPATIBILITY** Eaton UPS Companion  
software

## Additional specifications

**CONSTRUCTION TYPE** Free standing model

### PACKAGE CONTENTS

- UPS
- USB cable
- User manual
- Important safety instructions
- Limited warranty

**COLOR** Black

**EFFICIENCY AT MAX. LOAD** 95%

**SURGE PROTECTION** Yes

## Warranty and support

### STANDARD FACTORY WARRANTY

- 2-YEAR FACTORY WARRANTY
- -2 years
- -Parts, electronics, and batteries coverage
- -Standard ground shipping
- -Technical support

### EXTENDED SERVICE PLANS

- ADVANCED DEPOT EXCHANGE
- -5-YEAR DEPOT REPAIR: 5SW5Y-750UC
- -Expedited parts coverage for 5 years
- -Parts, electronics and UPS batteries coverage
- -Next business day shipping
- -Technical support

## Resources

### BROCHURES

[5-series UPS overview brochure](#)

[Eaton 5S UPS brochure](#)

### MANUALS AND USER GUIDES

[Eaton 5S UPS safety manual](#)

[Eaton 5S UPS 230V user manual](#)

### SPECIFICATIONS AND DATASHEETS

[Eaton 5S UPS technical specifications](#)

[Eaton Specification Sheet - 5S700G](#)

### WARRANTY GUIDES

[Eaton load protection guarantee](#)

[Eaton limited warranty](#)

[Eaton extended warranty certificate](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

