

Specifications



Eaton EMI200-10

Eaton Metered Input PDU, Split Phase, 0U, L14-30P input, 10ft cord, 5.76kW, 24A, 120/240V, 34 Outlets (20) C13 (6) C19 (8) 5-20R

General specifications

PRODUCT NAME	Eaton metered input PDU
CATALOG NUMBER	EMI200-10
UPC	786685913407
PRODUCT LENGTH/DEPTH	66.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	2.05 in
PRODUCT WEIGHT	0.0001 lb
WARRANTY	3 year
COMPLIANCES	TAA Compliant
CERTIFICATIONS	UL Listed
PRODUCT TYPE	Metered input PDU

Product specifications

FORM FACTOR	0U (Vertical)
OUTLET CONTROL	No
PHASE	Split-phase
WATTAGE	5.76 kW max
AMPERAGE RATING	24A
INPUT VOLTAGE	120/240V
INPUT CONNECTION	L14-30P
OUTLETS	(8) 5-20R, (20) C13 Outlet grip, (6) C19 Outlet grip
CORD LENGTH	10 ft
FREQUENCY RATING	50-60 Hz
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	RS-232
OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)

Resources

CERTIFICATION REPORTS	Eaton RoHS Declaration of Conformity: ePDU G3
DRAWINGS	Eaton ePDU G3 Metered Input EMI200-10 technical drawing
	Eaton ePDU G3 installation and connectivity quick start guide
	Eaton ePDU G3 instruction set - system objects
MANUALS AND USER GUIDES	Eaton ePDU G3 operations manual
	Eaton ePDU G3 EMP installation and connection quick start guide
SERVICE AND TROUBLESHOOTING	EMI200-10 eNMC replacement configuration file
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EMI200-10

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

