Product data sheet

Specifications



APC Smart-UPS Ultra On-Line, 2200VA, Lithium-ion, Rack/Tower 1U, 120V, 5x 5-20R, 1x L5-20R NEMA outlets, Network Card, Extended runtime, W/rail kit

SRTL2K2RM1UNC

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Main input voltage	120 V AC 1 phase 125 V AC 1 phase
Other input voltage	120 V 125 V
Input connection	NEMA 5-20P
Input frequency	50/60 Hz
Output voltage	120 V AC 1 phase 125 V AC 1 phase
Other output voltage	120 V 125 V
Rated power in W	1950 W
Rated power in VA	2200 VA
Output connection	5 NEMA 5-20R 1 NEMA L5-20R
Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1950 W
UPS topology	On-Line
Waveform type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC173-LI

Graphs

Runtime	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery type	Li-Ion (Lithium Ion) internal included
Control panel	Multi-function LCD status and control console
Emergency power off	Yes
Preinstalled device	Network management card with environmental monitoring

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port Embedded network management card 3
Number of rack unit	1U
Cable length	7.9 ft (2.4 m)
Number of cables	1
Color	Silver grey
Height	1.7 in (43 mm)
Width	17.008 in (432 mm)
Depth	22.05 in (560 mm)
Product weight	35.05 lb(US) (15.9 kg)
Mounting preference	No preference
Mounting mode	Rack-mounted with kit Tower-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting mode	Rack/tower convertible with included kit
Provided equipment	RJ45 Cable USB cable Country-specific detachable power cord Rack Mounting brackets Rack Mounting support rails Installation guide Warranty card
Redundant	No
Range of product	Smart-UPS Ultra
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	UL/cUL listed FCC
Standard	UL 1778 CSA C22.2 No.107.3-05 FCC Part 15 class A
Ambient air temperature for operation	32…104 °F (0…40 °C)
Ambient air temperature for storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0…15240 m)
IP protection	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Acoustic level	55 dB
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Li-Ion (Lithium Ion)
Battery voltage	50 V

Extendable runtime	1
Typical recharge time	1.5 h
RBC quantity	1
Battery charging power	448 W

Ordering and shipping details

GTIN	731304435563

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.9 in (27.8 cm)
Package 1 Width	22.2 in (56.4 cm)
Package 1 Length	30.08 in (76.4 cm)
Package weight(Lbs)	53.31 lb(US) (24.18 kg)

Contractual warranty

Warranty (in months)	60

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**5 818 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 250 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**7 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**9 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**4 521 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**31 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**8c493f2b-82c6-495f-a54a-f7d594e2b537**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**52**
Circularity Profile	End of Life Information
Removable battery	**User replaceable**
Take-back	**Yes**

Image of product / Alternate images

Alternative













Product data sheet SRTL2K2RM1UNC

