Product data sheet

Specifications



APC NetShelter Switched Rack PDU, 2U, 30A, 120V, 16 NEMA 5-20 outlet

AP7902B

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	PDU
Main Input Voltage	100 V 120 V
Input current limits	30 A
Input Frequency	50/60 Hz
Main Output Voltage	120 V
Input Connection Type	NEMA L5-30P
Number of power socket outlets	16 NEMA 5-20R
Load Capacity	2880 VA
Line Rated Current	24 A
permissible voltage	100…120 V
Max current draw	30 A
PDU Type	Switched
Number of rack unit	2U
Number of cables	1
Cable length	9.8 ft (3 m)
Provided Equipment	Cord retention bracket(s) Horizontal mounting brackets User Manual Installation guide

Complementary

Mounting Location	Front Rear
Mounting Mode	Rack-mounted
Mounting position	Horizontal
Height	3.5 in (89 mm)
Width	17.5 in (445 mm)
Depth	4.5 in (114 mm)
Net Weight	9.9 lb(US) (4.5 kg)

Environmental

Product Certifications	cUL Listed CSA Industry Canada UL Listed

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	FCC Part 15 class A ICES-003 UL 60950
Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32…113 °F (0…45 °C)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304331582
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.5 in (14 cm)
Package 1 Width	14.5 in (36.8 cm)
Package 1 Length	20.0 in (50.8 cm)
Package weight(Lbs)	14.44 lb(US) (6.55 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**1 994 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**36 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 954 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**3 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**
Halogen content performance	**Product contains halogen above thresholds**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**71**
Circularity Profile	**End of Life Information**
Removable battery	**Yes**
Take-back	**No**

WEEE Label	 **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative






APC
APC