Product data sheet

Specifications



APC NetShelter Metered Rack PDU, 0U, 3PH, 11kW 230V 16A or 11kW 230V 16A, 36 C13 and 6 C19 outlets, IEC 309 3P+N+PE cord

AP8881

Overview

Presentation	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Main

Product or Component Type	PDU
Main Input Voltage	400 V 3 phase
Input current limits	16 A
Input Frequency	50/60 Hz
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 3P+N+PE IEC 60309 20 A 3P+N+PE
Number of power socket outlets	36 IEC 60320 C13 6 IEC 60320 C19
Load Capacity	11000 VA
Line Rated Current	16 A
Max current draw	16 A
Max line current	16 A
PDU Type	Metered
Protection Type	Without circuit breaker
Number of rack unit	0U
Number of cables	1
Cable length	5.97 ft (1.82 m)
Provided Equipment	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

Complementary

Mounting Location	Side

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Mode	Rack-mounted
Mounting position	Vertical
Height	70.5 in (1791 mm)
Width	2.2 in (55 mm)
Depth	1.7 in (44 mm)
Net Weight	14.07 lb(US) (6.38 kg)

Environmental

Product Certifications	VDE
Standards	CSA C22.2 No. 60950 IEC 60950 UL 60950-1
Relative Humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	23…140 °F (-5…60 °C)

Ordering and shipping details

GTIN	731304277071
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	78.7 in (200 cm)
Package 1 Width	6.4 in (16.2 cm)
Package 1 Length	4.2 in (10.7 cm)
Package weight(Lbs)	17.68 lb(US) (8.02 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2 028 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**114 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.3 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 909 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**
Halogen content performance	**Product contains halogen above thresholds**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**53**
Circularity Profile	**End of Life Information**
Removable battery	**Yes**
Take-back	**No**

WEEE Label	 **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



