Product data sheet

Specifications



APC NetShelter Basic Rack PDU, Zero U, 20A, 120V, 14 NEMA 5-15 outlets

AP9551

Main

Product or Component Type	PDU
Main Input Voltage	100 V 120 V
Input current limits	20 A
Input Frequency	50/60 Hz
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number of power socket outlets	14 NEMA 5-15R
Load Capacity	1920 VA
Line Rated Current	16 A
permissible voltage	90…132 V
Max current draw	20 A
Max line current	20 A
PDU Type	Basic
Protection Type	Circuit breaker
Number of rack unit	0U
Number of cables	1
Cable length	11.98 ft (3.65 m)
Provided Equipment	Rack Mounting brackets Toolless Mounting Kit User Manual

Complementary

Mounting Location	Side
Mounting Mode	Rack-mounted
Mounting position	Vertical
Height	24.02 in (610 mm)
Width	1.7 in (42 mm)
Depth	1.7 in (44 mm)
Net Weight	4.9 lb(US) (2.2 kg)

Environmental

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	cUL Listed CSA UL Listed
Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32…113 °F (0…45 °C)

Ordering and shipping details

GTIN	731304021247

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	25.5 in (64.8 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	7.008 in (17.8 cm)
Package weight(Lbs)	6.44 lb(US) (2.92 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**1 750 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 739 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen content performance	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**45**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**