Product data sheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 15A, 120V, 10 NEMA 5-15 outlets

AP9562

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	PDU
Main Input Voltage	100 V 120 V
Input current limits	15 A
Input Frequency	50/60 Hz
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Number of power socket outlets	10 NEMA 5-15R
Load Capacity	1400 VA
Line Rated Current	12 A
Max current draw	15 A
PDU Type	Basic
Number of rack unit	1U
Number of cables	1
Cable length	11.98 ft (3.65 m)
Provided Equipment	Installation guide Rack Mounting brackets

Complementary

Mounting Location	Front Rear
Mounting Mode	Rack-mounted
Mounting position	Horizontal
Height	1.7 in (44 mm)
Width	17.6 in (447 mm)
Depth	2.2 in (57 mm)
Net Weight	5.5 lb(US) (2.5 kg)

Environmental

Product Certifications	cUL Listed METI Denan UL Listed
Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	23…113 °F (-5…45 °C)

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304203865
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.8 in (7 cm)
Package 1 Width	9.02 in (22.9 cm)
Package 1 Length	18.3 in (46.4 cm)
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**114 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**102 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Product contains halogen above thresholds**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**45**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**