Product data sheet

Specifications



APC Replacement Battery Cartridge, VRLA battery, 7Ah, 12VDC, 2-year warranty

APCRBC110

Main

Product or Component Type	Replacement battery cartridge
Battery Type	Lead-Acid battery
Provided Equipment	All required connectors Battery recycling guide Reusable packaging Installation guide

Batteries & Runtime

Included Battery Modules	0
Device mounting	Enclosed battery cabinet
Battery Voltage	12 V
RBC Quantity	1

Physical

Color	Black
Height	4.1 in (105 mm)
Width	5.9 in (151 mm)
Depth	2.6 in (65 mm)
Net Weight	4.9 lb(US) (2.2 kg)
Mounting Mode	Not rack-mountable
USB compatible	No

Output

Battery Capacity	7.0 Ah

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0…95 %
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0…15240 m)
Storage Relative Humidity	0…95 %

Ordering and shipping details

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	731304248217

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.228 in (8.200 cm)
Package 1 Width	6.890 in (17.500 cm)
Package 1 Length	8.268 in (21.000 cm)
Package weight(Lbs)	5.150 lb(US) (2.336 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	150
Package 2 Height	38.189 in (97.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	803.365 lb(US) (364.400 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**16 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**8 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0.8 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**6 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**1**
Circularity Profile	End of Life Information
Removable battery	**No**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

