Product data sheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 18U, Black, 925H x 600W x 900D mm [TAA]

AR3006

Overview

Presentation	An industry-standard rack with the most standard features for speed of deployment and installation. Ready for low to medium density edge computing. Shorter height allows for deployment underneath cabinets, desks, in remote office branch office spaces for a secure and discrete solution for IT devices.

Main

Product or Component Type	Rack enclosure
Number of rack unit	18U
Rack Width	19"
Permanent permissible load	900 lb(US) (408.2 kg) dynamic 900 lb(US) (408.2 kg) static
Provided equipment	Casters Doors Key(s) Leveling feet Roof Side Panels

Complementary

Mounting Mode	Not rack-mountable
Minimum Mounting Depth	7.5 in (191 mm)
Maximum Mounting Depth	29.8 in (755.7 mm)
Color	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	36.4 in (925 mm)
Width	23.6 in (600 mm)
Depth	35.4 in (900 mm)
Net Weight	148.00 lb(US) (67.13 kg)

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E

Ordering and shipping details

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	731304347651

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	41.7 in (106 cm)
Package 1 Width	39.2 in (99.5 cm)
Package 1 Length	29.5 in (75 cm)
Package weight(Lbs)	189.6 lb(US) (86 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS

Contractual warranty

Warranty (in months)	60

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**302 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**288 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**7 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**6 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



