Product data sheet

Specifications



To be discontinued

APC NetShelter SX, Server Rack Enclosure, 42U, Black, 1991H x 600W x 1200D mm

AR3300

Discontinued on: Dec 31, 2025

To be end-of-service on: Feb 14, 2029

Main

Product or Component Type	Rack enclosure
Number of rack unit	42U
Rack Width	19"
Permanent permissible load	2250 lb(US) (1020.6 kg) dynamic 3750 lb(US) (1701.0 kg) static
Provided equipment	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels

Complementary

Mounting Mode	Not rack-mountable
Minimum Mounting Depth	7.5 in (190.5 mm)
Maximum Mounting Depth	41.3 in (1048 mm)
Color	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	78.4 in (1991 mm)
Width	23.6 in (600 mm)
Depth	47.2 in (1200 mm)
Net Weight	295.62 lb(US) (134.09 kg)

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E

Ordering and shipping details

GTIN	731304256274

Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	83.4 in (211.8 cm)
Package 1 Width	29.6 in (75.2 cm)
Package 1 Length	52.5 in (133.4 cm)
Package weight(Lbs)	328.69 lb(US) (149.09 kg)

Contractual warranty

Warranty (in months)	60

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**523 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**499 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**13 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**11 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative






35
34
33
32
31


35
34
33
32
31
30


35
34
33
32
31
30


37















