Product data sheet

Specifications



APC NetShelter CX, Fan booster Kit, Includes Replacement Power Supply and Fan Tray, Black

AR4703

Overview

Presentation	The NetShelter CX Fan Booster Kit is a user-fitted accessory which will increase the thermal capacity of the NetShelter CX. Allowing for more density of equipment, such as Blade Servers & high-density Switches. This Booster Kit consists of a replacement Power Supply Unit - PSU (24V) and a replacement Fan Tray. One Kit is needed per Fan Unit. Compatible with all generations of NetShelter CX 18U, 24U & 38U - this Kit can be retro-fitted to NetShelter CX already in the field, or to newly purchased NetShelter CX units. New Thermal loadings 18U : 1200 Watts > 2400 Watts, 24U : 2400 Watts > 3500 Watts, 38U : 3600 Watts > 5000 Watts

Main

Main Input Voltage	100 V 115 V 120 V 200 V 208 V 220 V 230 V 240 V
Input Connection Type	IEC 60320 C14
Provided equipment	Installation guide

Physical

Color	Black
Height	5.9 in (15 cm)
Width	17.9 in (45.5 cm)
Depth	6.3 in (16 cm)
Net Weight	4.4 lb(US) (2 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	47...63 Hz

Conformance

Product Certifications	TAA compliance

Ordering and shipping details

GTIN	731304309819

Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.8 in (25 cm)
Package 1 Width	22.05 in (56 cm)
Package 1 Length	11.02 in (28 cm)
Package weight(Lbs)	6.380 lb(US) (2.894 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**10 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**10 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

