Product data sheet

Specifications



APC Back-UPS Pro External Battery Pack

BR24BPG

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Main Input Voltage	120 V
Product or Component Type	External battery pack
Number of cables	1
Battery Type	Lead-Acid battery
Provided Equipment	User Manual
Range of Product	Back-UPS Pro

Batteries & Runtime

Device mounting	Stand alone battery stack
Battery Life	4…6 year(s)
Battery Voltage	24 V
Battery Capacity	18 Ah
Included Battery Modules	2
Battery Slots Empty	0
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	372 VAh

Physical

Color	Black
Height	11.9 in (301 mm)
Width	4.4 in (112 mm)
Depth	15.04 in (382 mm)
Net Weight	29.5 lb(US) (13.4 kg)
USB compatible	No

Conformance

Product Certifications	TÜV

Environmental

Relative Humidity	0…95 %
Storage Relative Humidity	0…95 %
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Operating altitude	0...30000 ft
Storage altitude	0…50000 ft (0…15240 m)

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304268789
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	15.748 in (40.000 cm)
Package 1 Width	9.449 in (24.000 cm)
Package 1 Length	19.331 in (49.100 cm)
Package weight(Lbs)	32.119 lb(US) (14.569 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	3
Package 2 Height	20.472 in (52.000 cm)
Package 2 Width	23.622 in (60.000 cm)
Package 2 Length	31.496 in (80.000 cm)
Package 2 Weight	111.790 lb(US) (50.707 kg)
SCC14	10731304268786

Contractual warranty

Warranty (in months)	36 UPS|12 Battery

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**67 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**54 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**4 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**51 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**5 kg CO2 eq.**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**1068e1eb-6a97-4f67-a95e-95f440cdd7dd**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**48**
Circularity Profile	End of Life Information
Removable battery	**No**
Take-back	**Yes**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



