Product data sheet

Specifications



APC KVM 2G, Digital/IP, 1 Remote/1 Local User, 16 Ports with Virtual Media - FIPS 140-2

KVM1116R

Main

Product or Component Type	Switch
Main Input Voltage	24 V DC 100 V 120 V 208 V 230 V 240 V
Input Frequency	50/60 Hz
Number of rack unit	1U

Complementary

Mounting Location	Front
Mounting Mode	Not rack-mountable
Color	Black
Height	1.7 in (43 mm)
Width	16.7 in (424 mm)
Depth	7.4 in (188 mm)
Net Weight	5.71 lb(US) (2.59 kg)

Environmental

Product Certifications	C-tick CE EAC TAA compliance UL-AR VCCI Class A VDE
Standards	FCC Part 15 class A ICES-003 UL 60950-1
Relative Humidity	0…80 %
Storage Relative Humidity	0…80 %
Ambient Air Temperature for Storage	-4…140 °F (-20…60 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32…122 °F (0…50 °C)

Ordering and shipping details

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	731304340195

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.7 in (14.6 cm)
Package 1 Width	13.0 in (33 cm)
Package 1 Length	24.4 in (61.9 cm)
Package weight(Lbs)	8.80 lb(US) (3.99 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**9 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**9 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative

