Product data sheet

Specifications



APC Smart-UPS SRT 192V 8 and 10kVA RM Battery Pack

SRT192RMBP2

Main

Product or Component Type	External battery pack
Number of rack unit	3U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide Warranty card Rack Mounting brackets
Range of Product	Smart-UPS Battery Systems
Replacement battery	APCRBC140

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	+/- 192 V
RBC Quantity	2

Physical

Color	Black
Height	5.1 in (130 mm)
Width	17.008 in (432 mm)
Depth	26.9 in (682.7 mm)
Net Weight	200.6 lb(US) (91 kg)
Mounting Mode	Rack-mounted
Two post mountable	1

Output

Battery Capacity	10 Ah

Conformance

Standards	OSHPD

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative Humidity	0…95 % non-condensing
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0…15240 m)
Storage Relative Humidity	0…95 % non-condensing

Ordering and shipping details

GTIN	731304292753

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	16.5 in (42 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	39.4 in (100 cm)
Package weight(Lbs)	232.6 lb(US) (105.5 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**483 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**390 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**26 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**30 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**368 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**37 kg CO2 eq.**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**488c31fb-3af8-42cf-9558-1362d000a07e**
EU RoHS Directive	Compliant
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**48**
Circularity Profile	End of Life Information
Removable battery	**User replaceable**
Take-back	**Yes**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



