Product data sheet

Specifications



APC Smart-UPS Step-Down Transformer, 5kVA, rackmount, 2U, 12x NEMA 5-20R outlets

SRT5KRMTF

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Main Input Voltage	208 V
Product or Component Type	Transformer
Main Output Voltage	120 V
Input Connection Type	NEMA L6-30P
Number of rack unit	2U
Number of cables	1
Provided Equipment	Mounting Hardware Rack Mounting brackets User Manual Warranty card
Range of Product	Smart-UPS Accessories

Physical

Color	Black
Height	3.5 in (89 mm)
Width	17.008 in (432 mm)
Depth	25.08 in (637 mm)
Net Weight	95.00 lb(US) (43.09 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Horizontal

Input

Max line current	24 A
Input current limits	30 A
Load Capacity	5000 VA

Output

Max current draw	24 A
Number of power socket outlets	12
Number of power socket outlets	12 NEMA 5-20R

Conformance

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	CSA
Standards	UL 1778

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Relative Humidity	0…95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5…113 °F (-15…45 °C)
Storage Relative Humidity	0…95 % non-condensing
Storage altitude	0…50000 ft (0…15240 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304318866
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.0 in (25.4 cm)
Package 1 Width	37.5 in (95.2 cm)
Package 1 Length	24.5 in (62.2 cm)
Package weight(Lbs)	110.01 lb(US) (49.9 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**4 541 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**176 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**4 358 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**3 kg CO2 eq.**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**A64c500c-f72a-458b-8faa-8175a94429fe**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**86**
Circularity Profile	**End of Life Information**
Take-back	**Yes**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative



