Product data sheet

Specifications



APC Smart-UPS Modular Ultra On-Line, 15kW, Lithium-ion, Tower 24U, 208/240V, Network Management Card

SRYL15K15XLT24

Main

Main input voltage	208 V AC 1 phase 120 V AC 1 phase 240 V AC 1 phase
Other input voltage	240 V
Maximum input current	75 A
Load power factor	0.5 leading to 0.5 lagging
Input connection	1 Hard Wire 4-wire (2PH+N+G)
Input frequency	40 - 70 Hz
Output voltage	120 V AC 1 phase 208 V AC 1 phase 240 V AC 1 phase
Other output voltage	240 V
Rated power in W	15000 W
Rated power in VA	15000 VA
Bypass type	Built-in Bypass
Maximum configurable power in VA	15000 VA
Maximum configurable power in W	15000 W
Output overload operation	60 seconds @ 125% and 30 seconds @ 150%
UPS topology	On-Line
Waveform type	Sine wave

Graphs

Runtime	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery type	Li-Ion (Lithium Ion) internal included
Control panel	Touch Screen LCD User Interface
Emergency power off	Yes
Preinstalled device	Network management card
UPS connectivity	Serial port USB port Available expansion slot Embedded network management card 3
Number of rack unit	24U

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Color	Black and silver
Height	47.2 in (1198 mm)
Width	23.6 in (600 mm)
Depth	35.4 in (900 mm)
Product weight	470.5 lb(US) (213.4 kg)
Mounting location	Front
Mounting mode	Tower
Number of power modules	3
Number of preinstalled power modules	3
Additional specification	Network management card
Range of product	Smart-UPS Modular Ultra
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	ENERGY STAR V2.0 (USA)
Ambient air temperature for operation	32…104 °F (0…40 °C)
Ambient air temperature for storage	5…113 °F (-15…45 °C)
Storage altitude	0…49212.6 ft (0…15000 m)
Storage relative humidity	0…95 %
Acoustic level	68 dB
Operating altitude	0...9842.52 ft (0...3000 m)

Batteries & Runtime

Battery type	Li-Ion (Lithium Ion)
Extendable runtime	0
Included battery module	3
RBC quantity	3
Battery design life	8…10 year(s)

Ordering and shipping details

GTIN	731304622123

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	52.05 in (132.2 cm)
Package 1 Width	29.4 in (74.6 cm)
Package 1 Length	39.2 in (99.5 cm)
Package weight(Lbs)	519.76 lb(US) (235.76 kg)

Contractual warranty

Warranty (in months)	60

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**37 516 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**9 505 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**124 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**89 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**27 304 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**494 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**31346aed-552c-4a16-81d9-e683a383b6da**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.**

Energy efficiency

Optimized Energy Efficiency	**Energy efficient product**
ENERGY STAR®	**ENERGY STAR UPS V2.0 (USA)**
Product contributes to saved and avoided emissions	**Yes**

Use Again

Repack and remanufacture

Recyclability potential, in %	**61**
Circularity Profile	End of Life Information
Removable battery	**User replaceable**
Take-back	**Yes**

Image of product / Alternate images

Alternative

