



Fire Alarm Cable

18/6C Solid CM/FPL, Red

4U1806S3B5

1.0 Scope

18 AWG, 6 conductor, solid bare copper fire alarm cable with SRPVC insulation and a red PVC jacket, rated CM/FPL, for 500 ft reel-in-box packaging.

2.0 Conductors

Material 18 AWG solid bare copper
Quantity 6 conductors

2.1 Insulation

Material SRPVC
Thickness 0.007" nom.
Color Code Black, White, Green, Yellow, Red, Blue

2.2 Cabling

Lay Length 4"
Shielding None

2.3 Jacket

Material PVC
Thickness 0.015" nom.
Color Red

2.4 Surface Printing

Print PAIGE USA 4U1806S3B5 18/6C SOL FIRE
CM/FPL ETL C(ETL) 400479 75C ROHS
COMPLIANT ZONE 0 1 2 3 4 5 6 7 8 9
(MFD DATE CODE)
(ASCENDING/DESCENDING FOOTAGE
MARK)

3.0 Rating and Approvals

Rating CM/FPL
Listing ETL / C(ETL) 400479
Test Req. UL 444, UL 1424
RoHS Compliant

4.0 Packaging

Type Reelex box
Length 500 ft

REVISIONS

ECO	REV	DATE	BY	DESCRIPTION
1329	A	03/05/2025	GJK	Initial release

Part #: 4U1806S3B5 Drawn by: GJK Date: 03/05/2025 Rev: A
Scale: None Sheet: 1 of 1

We want to hear from you!

200 Sheffield St, Suite 302, Mountainside, NJ 07092

Tel: 888.423.8947 gamechanger@paigeelectric.com

